

Babel support for the Greek language

Apostolos Syropoulos, Günter Milde

November 10, 2020

Babel-greek is a contributed package providing support for the Greek language and script via the [Babel](#) system. See the [README](#) file for an overview of the `babel-greek` package and links to requirements and related packages.

The file `babel-greek.dtx`¹ is the literate source for the Babel language definition file `greek.ldf`.

1 Requirements

Typesetting Greek with Babel requires (of course) the [Babel core](#), support for Greek font encodings ([greek-fontenc](#)) and a [text font supporting the Greek script](#).

The [CB Greek fonts](#) created by CLAUDIO BECCARI² are a complete set of 8-bit TeX fonts matching KNUTH's Computer Modern. The package `cbfonts-fd` sets them up as Greek substitute for the Computer Modern and Latin Modern font families. The `substitutefont` package can be used to set up Greek supplements for other font families (like Times or Palatino).

The [Latin Modern](#) OpenType font that is the default font for XeTeX/LuaTeX does not support the Greek script. The user needs to set up an alternative font like CM Unicode, Linux Libertine or DejaVu with [fontspec](#).

2 Usage

To activate Greek support with babel, specify the option `greek`, either as global option or as option to the `babel` package. Remember, that the *last* language option determines the document language, e.g.

```
\usepackage[greek,english]{babel}
```

activates support for Greek in an English document. The default is modern "monotonic" Greek, while

¹The file described in this section has version number v1.10 and was last revised on 2020/11/10. The original author is Apostolos Syropoulos, code from `kdgreek.sty` by David Kastrup was used.

²Apostolos Syropoulos wishes to thank Claudio Beccari for his patience, collaboration, comments and suggestions.

```
\usepackage[english,greek]{babel}
\languageattribute{greek}{polutoniko}
```

sets the document language to modern Greek with “polytonic” spelling and

```
\usepackage[english,greek]{babel}
\languageattribute{greek}{ancient}
```

sets the document language to ancient Greek.

Both attributes may also be used as modifiers as in

```
\usepackage[greek.polutoniko,english]{babel}
```

and similarly

```
\usepackage[greek.ancient,english]{babel}
```

By default, `babel-greek` activates the modern Greek monotonic hyphenation; the attribute/modifier `polutoniko` activates the modern Greek polytonic hyphenation and the attribute/modifier `ancient` activates the ancient Greek hyphenation. 8-bit TeX and XeTeX require the hyphenation patterns to be pre-loaded in the format file. This is a limitation by TeX, common to all languages. The LuaTeX engine loads hyphenation patterns on demand.

```
\selectlanguage
\foreignlanguage
```

The Babel core provides two commands to switch the active language: The declaration `\selectlanguage{greek}` switches to the Greek language. The macro `\foreignlanguage{greek}{<some text>}` sets its second argument in the Greek language. This is intended for short text parts. For details see the [Babel documentation](#).

For backwards compatibility, “polytonic” spelling can also be selected via the dummy language `polutonikogreek`. In this case, the language name `polutonikogreek` must also be used for language switches with `\selectlanguage` or `\foreignlanguage`. However, it is not possible to use both options, `greek` and `polutonikogreek` in one document.

2.1 Input of Greek text

There are several alternatives to write Greek text.

- With the packages `inputenc` and `greek-inputenc`, literal Greek characters can be input using the utf-8, iso-8859-7, or macgreek encoding.
Literal input using the utf-8 encoding is also the standard input method if compiling with the XeTeX and LuaTeX engines.
- The Latin transliteration defined by the LGR font encoding is explained in the file [usage.pdf](#).

- The package `greek-fontenc` defines *LaTeX internal character representation* (LICR) macros for Greek letters and text symbols. It is required by `babel-greek`, so the `\textAlpha ... \textOmega` macros are a safe but cumbersome method to input Greek characters.
- The `alphabeta` package bundled with `greek-fontenc` makes the short macro names `\Alpha ... \Omega` available in text mode, too.

The `greek-fontenc` bundle has details and examples for all these input methods.

2.2 Greek vs. Latin script

When switching the language to Greek, `babel-greek` ensures that the Greek script is supported. With 8-bit LaTeX, Greek text fonts use a non-standard font encoding³ (LGR) that misses Latin letters. Latin characters in the source are instead interpreted as a transcription for Greek characters. The following macros allow the use of Greek vs. Latin script without changing the active language. The *TextCommand*⁴ `\greekscript` switches to a font encoding supporting the Greek script. The declaration `\greektext` always switches the font encoding to LGR. Both declarations do not change the active language. `\latintext` (defined by the Babel core) can be used to switch back to an encoding supporting the Latin script (deprecated since Babel 3.9i from March 2014).

```
\greekscript
\greektext
\latintext
\ensuregreek
\textgreek
\textlatin
```

The macros `\ensuregreek` and `\textgreek` take one argument which is typeset using a font encoding supporting the Greek script. While `\ensuregreek` only switches the font encoding if required, `\textgreek` always uses the LGR font encoding. The Babel core defines a corresponding `\textlatin` macro (deprecated in favour of `\ensureascii` in Babel 3.9i from March 2014).

3 Greek numbering

The Greek alphabetical numbering system, like the Roman one, is still used in everyday life for short enumerations. Unfortunately most Greeks don't know how to write Greek numbers bigger than 20 or 30. Nevertheless, in official editions of the last century and beginning of this century this numbering system was also used for dates and numbers in the range of several thousands. Nowadays this numbering system is primarily used by the Eastern Orthodox Church and by certain scholars. It is hence necessary to be able to typeset any Greek numeral up to 999 999. Here are the conventions:

- There is no Greek numeral for any number less than or equal to 0.
- Numbers from 1 to 9 are denoted by letters alpha, beta, gamma, delta, epsilon, stigma, zeta, eta, theta, followed by a mark similar to the mathematical symbol “prime”. (Nowadays instead of letter stigma the digraph

³LaTeX font encodings are described in the *LaTeX font guide* (fntguide.pdf).

⁴For a discussion of TextCommands, see the *LaTeX font guide* (fntguide.pdf), too.

sigma tau is used for number 6. Mainly because the letter stigma is not always available, so people opt to write down the first two letters of its name as an alternative. In our implementation we produce the letter stigma, not the digraph sigma tau.)

- Decades from 10 to 90 are denoted by letters iota, kappa, lambda, mu, nu, xi, omikron, pi, qoppa, again followed by the numeric mark. The qoppa used for this purpose has a special zig-zag form, which doesn't resemble at all the original 'q'-like qoppa.
- Hundreds from 100 to 900 are denoted by letters rho, sigma, tau, upsilon, phi, chi, psi, omega, sampi, followed by the numeric mark.
- Any number between 1 and 999 is obtained by a group of letters denoting the hundreds decades and units, followed by a numeric mark.
- To denote thousands one uses the same method, but this time the mark is placed in front of the letter, and under the baseline (it is inverted by 180 degrees). When a group of letters denoting thousands is followed by a group of letters denoting a number under 1000, then both marks are used.

`\greeknumeral` Using these conventions one obtains numbers up to 999 999. The command `\greeknumeral` makes it possible to typeset Greek numerals. There is also an "uppercase" version of this macro: `\Greeknumeral`.

Another system which was in wide use only in Athens, could express any positive number. This system is implemented in package `athnum`.

4 Implementation

The macro `\LdfInit` takes care of preventing that this file is loaded more than once, checking the category code of the @ sign, etc.

```
1 {*code}
2 \LdfInit\CurrentOption{captions\CurrentOption}
```

When the option `polotonikogreek` was used, redefine `\CurrentOption` to prevent problems later on.

```
3 \gdef\CurrentOption{greek}
```

Hyphenation patterns: When this file is read as an option, i.e. by the `\usepackage` command, `greek` could be an 'unknown' language in which case we have to make it known. So we check for the existence of the three variants of the Greek language `\l@greek`, `\l@monogreek`, and `\l@ancientgreek` to see whether we have to do something here.

```
4 \ifx\l@greek\@undefined
5   \@nopatterns{greek}
6   \adddialect\l@greek 0\fi
7 \ifx\l@monogreek\@undefined
8   \adddialect\l@monogreek 0\fi
```

```

9 \ifx\l@ancientgreek\@undefined
10   \adddialect\l@ancientgreek 0\fi
11 \newcount\bbl@monogreek \bbl@monogreek=\l@monogreek
12 \newcount\bbl@polygreek \bbl@polygreek=\l@greek
13 \newcount\bbl@ancientgreek \bbl@ancientgreek=\l@ancientgreek

```

The `\extrasgreek` macro is called when switching the language to Greek. We collect code for polytonic and ancient greek in the macros `extraspolutonikogreek` and `extrasancientgreek` and add it later to `extrasgreek`.

```

14 \addto\extrasgreek{\let\l@greek\bbl@monogreek\relax}
15 \addto\extraspolutonikogreek{\l@greek=\bbl@polygreek}
16 \addto\extrasancientgreek{\l@greek=\bbl@ancientgreek}

```

Now we declare the `polutoniko` language attribute.

```
17 \bbl@declare@ttribute{greek}{polutoniko}{%
```

This code adds the expansion of `\extraspolutonikogreek` to `\extrasgreek` and changes the definition of `\today` for Greek to produce polytonic month names (by re-defining `\gr@month`).

```

18 \expandafter\addto\expandafter\extrasgreek
19   \expandafter{\extraspolutonikogreek}%
20 \let\captionsgreek\captionspolutonikogreek
21 \let\gr@month\gr@c@month

```

We need to take some extra precautions in order not to break older documents which still use the old `polutonikogreek` pseuso-language option: language switching commands like `\selectlanguage{polutonikogreek}`, call the `extraspolutonikogreek` macro, set the language to `\l@polutonikogreek` and use `\datepolutonikogreek` for `\today`. We define aliases:

```

22 \let\l@polutonikogreek\l@greek
23 \let\datepolutonikogreek\dategreek
24 \let\extraspolutonikogreek\extrasgreek
25 \let\noextraspolutonikogreek\noextrasgreek
26 }

```

The `ancient` language attribute is used for classical Greek.

```
27 \bbl@declare@ttribute{greek}{ancient}{%
```

This attribute adds the expansion of `\extraspolutonikogreek` and `\extrasancientgreek` to `\extrasgreek` to set up support for multi-accented characters and ancient hyphenation patterns. Auto-strings (captions) are specific to ancient Greek while `\today` uses modern polytonic month names (as there existed incompatible sets of month names and no common calendar in ancient Greece).

```

28 \expandafter\addto\expandafter\extrasgreek
29   \expandafter{\extraspolutonikogreek}%
  multi-accented letters
30 \expandafter\addto\expandafter\extrasgreek
31   \expandafter{\extrasancientgreek}%
32 \let\captionsgreek\captionsancientgreek
33 \let\gr@month\gr@c@month % (modern) polytonic month names
34 }

```

5 Font setup

Typesetting Greek texts requires a font with Greek characters:

For 8-bit LaTeX, this package uses fonts with the [LGR font encoding](#). With the XeTeX or LuaTeX engines and Unicode fonts, the user must ensure that the selected font contains the required glyphs. LGR-encoded fonts can also be used alongside Unicode fonts with XeTeX/LuaTeX to enable the input of Greek letters via the Latin transcription provided by this font encoding.

\greekfontencoding

We test for available font encodings and set \greekfontencoding and the internal macro \bbl@greek@fontencdef with the name of the font definition file with Greek LICR macros. The default is LGR for 8-bit TeX engines and TU for Xe/LuaTeX. (TODO: The font encoding definition file was renamed to tuenc-greek.def in *greek-fontenc* 0.14 (2020-02-28).)

```
35 \ifdefined \UnicodeEncodingName % set by LaTeX for Unicode-aware engines
36   \providecommand*\greekfontencoding{\UnicodeEncodingName}
37   \providecommand*\bbl@greek@fontencdef{tuenc-greek}
38 \else
39   \providecommand*\greekfontencoding{LGR}
40   \providecommand*\bbl@greek@fontencdef{lgrenc}
41 \fi
```

Ensure that the Greek LICR macros are available:

```
42 \@ifl@aded{def}{\bbl@greek@fontencdef{}}
43 {%
44   \InputIfFileExists{\bbl@greek@fontencdef .def}{}{%
45     \bbl@error{Font support for the Greek script missing.\\
46       babel-greek can't typeset Greek.\\
47       Install the "greek-fontenc" package\\
48       or use XeTeX/LuaTeX with polyglossia.}%
49     {I can't find the \bbl@greek@fontencdef .def file
50      for the Greek fonts (encoding \greekfontencoding)}%
51   }%
52 }%
53 }
```

\greekscript

The TextCommand \greekscript is a declaration that switches the font encoding to \greekfontencoding if the current font encoding does not provide a (typically empty) local variant.

```
54 \ProvideTextCommandDefault{\greekscript}{%
55   \fontencoding{\greekfontencoding}\selectfont
56   \def\encodingdefault{\greekfontencoding}}
```

\ensuregreek

The TextCommand \ensuregreek sets its argument in \greekfontencoding if the current font encoding does not provide a (typically empty) local variant.

```
57 \ProvideTextCommandDefault{\ensuregreek}[1]{%
58   \leavevmode{\greekscript #1}}
```

The package hyperref defines the PU font encoding which supports monotonic Greek. Load support for polytonic greek, archaic symbols, and the \greekscript and \ensuregreek TextCommands:

```

59 \AtBeginDocument{
60   \@ifl@aded{def}{puenc}{
61     \makeatletter % required inside \AtBeginDocument
62     \InputIfFileExists{puenc-greek.def}{}{%
63       \bbl@warning{I can't find the file puenc-greek.def from "greek-fontenc".}}
64     }
65     \makeatother
66   }{%
67 }
68 % \end{macrocode}
69 %
70 % \subsection{Fixes for the LGR font encoding}
71 %
72 % \begin{macrocode}
73 \@ifl@aded{def}{lgrenc}{%

```

We redefine a few commands in the LGR encoding to work around problems because LGR is no *standard text encoding* but has Greek letters in the places of Latin ones. The ampersand must work in text and math mode. We provide the text command \textampersand and re-define \& to use it in text mode.

```

74 \ProvideTextCommand{\textcopyright}{LGR}{\ensureascii{\textcopyright}}
75 \ProvideTextCommand{\textregistered}{LGR}{\ensureascii{\textregistered}}
76 \ProvideTextCommand{\texttrademark}{LGR}{\ensureascii{\texttrademark}}
77 \let\ltx@amp\&
78 \ProvideTextCommandDefault{\textampersand}{\ltx@amp}
79 \ProvideTextCommand{\textampersand}{LGR}{\ensureascii{\ltx@amp}}
80 \DeclareRobustCommand{\&}{{\ifmmode\ltx@amp\else\textampersand\fi}}
81 \ProvideTextCommand{\SS}{LGR}{\ensureascii{\SS}}

```

\greek@roman
\greek@Roman To prevent roman numerals being typeset in greek letters we need to adopt the internal L^AT_EX commands \croman and \CRoman. Up to version 1.5, the definition caused errors where *roman* ends up in a situation where the argument needs to be expanded (e.g. Roman page numbers in the ToC).

```

82 \def\croman#1{\expandafter\ensureascii\expandafter{\romannumeral#1}}
83 \def\CRoman#1{\expandafter\ensureascii\expandafter{%
84   \expandafter\@slowromancap\romannumeral#1@}}

```

Now we define two commands that switch to the LGR font encoding. The Babel core defines corresponding commands to switch to a Latin font encoding.

\greektext The declaration \greektext switches to LGR. For shorter pieces of text the \textgreek macro should be used.

```

85 \DeclareRobustCommand{\greektext}{%
86   \fontencoding{LGR}\selectfont
87   \def\encodingdefault{LGR}}

```

- \textgreek This command takes an argument which is then typeset using the LGR font encoding. In order to avoid many encoding switches it operates in a local scope.
- ```
88 \DeclareRobustCommand{\textgreek}[1]{\leavevmode{\greektext #1}}
```
- \textol The CB Greek fonts contain an outline family. In order to make it available, we define the command \textol. (This font-specific macro does not fit in a language definition file and only kept for backwards compatibility.)
- ```
89 \def\outlfamily{\usefont{LGR}{cmro}{m}{n}}
90 \DeclareTextFontCommand{\textol}{\outlfamily}
91 }{} % End of LGR fixes.
```

6 Definitions for the Greek language

The next step consists in defining commands to switch to (and from) the Greek language.

- \greekhyphenmins This macro is used to store the correct values of the hyphenation parameters \lefthyphenmin and \righthyphenmin.
- ```
92 % Yannis Haralambous has suggested this value
93 \providehyphenmins{\CurrentOption}{\@ne\@ne}
```
- \captionsgreek The macro \captionsgreek defines all strings used in the four standard document classes provided with L<sup>A</sup>T<sub>E</sub>X.
- ```
94 \addto\captionsgreek{%
95   \def\prefacename{\textPi\textrho\accc{\textnu}\textomicron\textlambda
96     \textomicron\textgamma\textomicron\textfinalsigma}%
97   \def\refname{\textAlpha\textnu\textalpha
98     \textphi\textomicron\textrho\accc{\textnu}\textepsilon\textfinalsigma}%
99   \def\abstractname{\textPi\textepsilon\textrho\accc{\textnu}\textiota
100    \textlambda\texteta\textpsi\texteta}%
101  \def\bibname{\textBeta\textiota\textbeta\textlambda\textiota\textomicron
102    \textgamma\textrho\textalpha\textphi\accc{\textnu}\textiota\textalpha}%
103  \def\chaptername{\textKappa\textepsilon\textrho\textphi\accc{\textnu}\textalpha
104    \textlambda\textalpha\textiota\textomicron}%
105  \def\appendixname{\textPi\textalpha\textrho\accc{\textnu}\textalpha\textrho\textalpha
106    \texttau\texteta\textmu\textalpha}%
107  \def\contentsname{\textPi\textepsilon\textrho\textphi\textiota
108    \textepsilon\textchi\accc{\textnu}\textomicron\textmu\textepsilon\textrho
109    \textnu\textalpha}%
110  \def\listfigurename{\textKappa\textalpha\texttau\accc{\textnu}\textalpha
111    \textlambda\textomicron\textgamma\textomicron\textfinalsigma}%
112  \def\textSigma\textchi\texteta\textmu\accc{\textnu}\textalpha\texttau
113    \textomega\textnu}%
114  \def\listtablename{\textKappa\textalpha\texttau\accc{\textnu}\textalpha
115    \textlambda\textomicron\textgamma\textomicron\textfinalsigma}%
116  \def\textPi\textiota\textnu\accc{\textnu}\textalpha\textkappa\textomega\textnu}%
117  \def\indexname{\textEpsilon\textupsilon\textrho\textepsilon\textiota
118    \texttau\accc{\textnu}\textalpha\texteta\textlambda\textomicron}%
}
```

```

119  \def\figurename{\textSigma\textchi\acctonos\texteta\textmu\textalpha}%
120  \def\tablename{\textPi\acctonos\textiota\textnu\textalpha
121    \textkappa\textalpha\textfinalsigma}%
122  \def\partname{\textMu\acctonos\textepsilon\textrho\textomicron
123    \textfinalsigma}%
124  \def\enclname{\textSigma\textupsilon\textnu\texteta\textmu
125    \textmu\acctonos\textepsilon\textrho\textalpha}%
126  \def\ccname{\textKappa\textomicron\textiota\textnu\textomicron
127    \textpi\textomicron\acctonos\textiota\texteta\textsigma\texteta}%
128  \def\headname{\textPi\textrho\textomicron\textfinalsigma}%
129  \def\pgname{\textSigma\textepsilon\textrho\textlambda\acctonos\textiota
130    \textdelta\textalpha}%
131  \def\seename{\textbeta\textlambda\acctonos\textepsilon\textpi\textepsilon}%
132  \def\alsoname{\textbeta\textlambda\acctonos\textepsilon\textpi\textepsilon{}}
133    \textepsilon\textpi\acctonos\textiota\textsigma\texteta\textfinalsigma}%
134  \def\proofname{\textAlpha\textpi\acctonos\textomicron
135    \textdelta\textepsilon\textiota\textxi\texteta}%
136  \def\glossaryname{\textGamma\textlambda\textomega\textsigma
137    \textsigma\acctonos\textalpha\textrho\textiota}%
138 }

```

\captionspolotonikogreek For texts written in the *πολυτονικό* (polytonic greek) the translations are the same as above, but some words are spelled differently. For now we just add extra definitions to \captionsgreek in order to override the earlier definitions.

```

139 \let\captionspolotonikogreek\captionsgreek
140 \addto\captionspolotonikogreek{%
141  \def\refname{\accpsili\textAlpha\textnu\textalpha
142    \textphi\textomicron\textrho\accvaria\textepsilon\textfinalsigma}%
143  \def\indexname{\textEpsilon\accasia\textupsilon\textrho\textepsilon\textpi
144    \texttau\acctonos\texteta\textrho\textiota\textomicron}%
145  \def\figurename{\textSigma\textchi\accperispomeni\texteta\textmu\textalpha}%
146  \def\headname{\textPi\textrho\accvaria\textomicron\textfinalsigma}%
147  \def\alsoname{\textbeta\textlambda\acctonos\textepsilon\textpi\textepsilon{}}
148    \accpsili\textepsilon\textpi\acctonos\textiota\textsigma\texteta\textfinalsigma}%
149  \def\proofname{\accpsili\textAlpha\textpi\acctonos\textomicron
150    \textdelta\textepsilon\textiota\textxi\texteta}%
151 }

```

\captionsancientgreek For texts written in ancient Greek, we took the translations from Apostolos Syropoulos' *xgreek* package. For now we just add extra definitions to \captionsgreek in order to override the earlier definitions.

```

152 \let\captionsancientgreek\captionsgreek
153 \addto\captionsancientgreek{%
154  \def\prefacename{\textPi\textrho\textomicron\textomicron\acctonos\textiota\textmu
155    \textiota\textomicron\textnu}%
156  \def\refname{\accpsili\textAlpha\textnu\textalpha\textphi\textomicron\textrho
157    \textalpha\accvaria\textiota}%
158  \def\abstractname{\textPi\textepsilon\textrho\acctonos\textiota\textlambda\texteta
159    \textpsi\textiota\textvarsigma}%

```

```

160 \def\bibname{\textBeta\textiota\textbeta\textlambda\textiota\textomicron
161   \textgamma\textrho\textalpha\textphi\accc\textiota\textalpha}%
162 \def\chaptername{\textKappa\textepsilon\textiota\textphi\accc\textiota\textalpha\textlambda
163   \textalpha\textiota\textomicron\textnu}%
164 \def\appendixname{\textPi\textalpha\textrho\accc\textalpha\textrho\texttau
165   \texteta\textmu\textalpha}%
166 \def\contentsname{\textPi\textepsilon\textiota\textrho\textiota\textepsilon\textiota\textchi
167   \accc\textomicron\textmu\textepsilon\textiota\textnu\textalpha}%
168 \def\listfigurename{\textKappa\textalpha\texttau\accc\textalpha\textlambda\textlambda
169   \textomicron\textgamma\textomicron\textvarsigma}%
170   \textsigma\textchi\texteta\textmu\accc\textalpha\texttau\textomega\textnu}%
171 \def\listtablename{\textKappa\textalpha\texttau\accc\textalpha\textlambda\textlambda
172   \textomicron\textgamma\textomicron\textvarsigma}%
173   \textpi\textiota\textnu\accc\textalpha\textkappa\textomega\textnu}%
174 \def\indexname{\textEpsilon\acc\textasia\textepsilon\textiota\textrho\textepsilon\textiota\texttau
175   \accc\texteta\textrho\textiota\textomicron\textnu}%
176 \def\figurename{\textSigma\textchi\acc\textperispomeni\texteta\textmu\textalpha}%
177 \def\tablename{\textPi\accc\textiota\textnu\textalpha\textxi}%
178 \def\partname{\textMu\accc\textepsilon\textiota\textrho\textomicron\textvarsigma}%
179 \def\enclname{\textSigma\textepsilon\textiota\textnu\texteta\textmu
180   \accc\textepsilon\textiota\textnu\textomega\textvarsigma}%
181 \def\ccname{\textKappa\textomicron\textiota\textnu\textomicron\textpi
182   \textomicron\accc\textiota\texteta\textsigma\textiota\textvarsigma}%
183 \def\headtoname{\textPi\textrho\acc\textvaria\textomicron\textvarsigma}%
184 \def\pagename{\textSigma\textepsilon\textiota\textlambda\acc\textvaria\textiota\textvarsigma}%
185 \def\seename{\acc\textasia\textoxia\textomicron\textrho\textalpha}%
186 \def\alsoname{\acc\textasia\textoxia\textomicron\textrho\textalpha} \acc\textasia\textomega\textsigma
187   \textalpha\accc\textepsilon\textiota\textnu\textomega\textvarsigma}%
188 \def\proofname{\acc\textpsili\textAlpha\textpi\accc\textalpha\textomicron\textdelta\textepsilon\textiota\textnu
189   \textiota\textxi\textiota\textvarsigma}%
190 \def\glossaryname{\textGamma\textlambda\textomega\textsigma\textsigma
191   \accc\textalpha\textrho\textiota\textomicron\textnu}%
192 }

```

- \gr@month The macro \dategreek redefines the command \today to produce greek dates.
 \dategreek The name of the month is now produced by the macro \gr@month since it is needed in the definition of the macro \Grtoday.

```

193 \def\gr@month{%
194   \ifcase\month\or
195     \textIota\textalpha\textnu\textomicron\textepsilon\textiota\textomicron\textupsilon\textalpha
196       \textrho\accc\textiota\textomicron\textupsilon\or
197     \textPhi\textepsilon\textiota\textbeta\textrho\textomicron\textupsilon
198       \textalpha\textrho\accc\textiota\textomicron\textupsilon\or
199     \textMu\textalpha\textrho\texttau\accc\textiota\textomicron\textupsilon
200     \or \textAlpha\textpi\textrho\textiota\textlambda\accc\textiota\textomicron\textupsilon
201       \textomicron\textupsilon\or
202     \textMu\textalpha\"{\textiota}\textomicron\textupsilon\or
203     \textIota\textomicron\textupsilon\textnu\accc\textiota\textomicron\textupsilon
204       \textomicron\textupsilon\or
205     \textIota\textomicron\textupsilon\textlambda\accc\textiota

```

```

206      \textomicron\textupsilon \or
207      \textAlpha\textupsilon\textgamma\textomicron\acctonos\textupsilon
208          \textsigma\texttau\textomicron\textupsilon \or
209      \textSigma\textepsilon\textpi\texttau\textepsilon\textmu
210          \textbeta\textrho\acctonos\textiota\textomicron\textupsilon \or
211      \textOmicron\textkappa\texttau\textomega\textbeta
212          \textrho\acctonos\textiota\textomicron\textupsilon \or
213      \textNu\textomicron\textepsilon\textmu\textbeta
214          \textrho\acctonos\textiota\textomicron\textupsilon \or
215      \textDelta\textepsilon\textkappa\textepsilon\textmu\textbeta
216          \textrho\acctonos\textiota\textomicron\textupsilon
217  fi
218 }
219 \def\dategreek{%
220   \def\today{\number\day \space \gr@month\space \number\year}}

```

\gr@c@greek

```

221 \def\gr@c@month{%
222   \ifcase\month\or
223     \accpsili\textIota\textalpha\textnu\textomicron\textupsilon\textalpha
224         \textrho\acctonos\textiota\textomicron\textupsilon \or
225     \textPhi\textepsilon\textbeta\textrho\textomicron\textupsilon
226         \textalpha\textrho\acctonos\textiota\textomicron\textupsilon \or
227     \textMu\textalpha\textrho\texttau\acctonos\textiota\textomicron
228         \textupsilon \or
229     \accpsili\textAlpha\textpi\textrho\textiota\textlambda
230         \acctonos\textiota\textomicron\textupsilon \or
231     \textMu\textalpha\'\textiota\textomicron\textupsilon \or
232     \accpsili\textIota\textomicron\textupsilon\textnu
233         \acctonos\textiota\textomicron\textupsilon \or
234     \accpsili\textIota\textomicron\textupsilon\textlambda
235         \acctonos\textiota\textomicron\textupsilon \or
236     \textAlpha\accpsili\textupsilon\textgamma\textomicron\acctonos
237         \textupsilon\textsigma\texttau\textomicron\textupsilon \or
238     \textSigma\textepsilon\textpi\texttau\textepsilon\textmu\textbeta
239         \textrho\acctonos\textiota\textomicron\textupsilon \or
240     \accpsili\textOmicron\textkappa\texttau\textomega\textbeta
241         \textrho\acctonos\textiota\textomicron\textupsilon \or
242     \textNu\textomicron\textepsilon\textmu\textbeta
243         \textrho\acctonos\textiota\textomicron\textupsilon \or
244     \textDelta\textepsilon\textkappa\textepsilon\textmu
245         \textbeta\textrho\acctonos\textiota\textomicron\textupsilon
246   fi
247 }

```

\Grtoday The macro \Grtoday produces the current date, only that the month and the day are shown as greek numerals instead of arabic as it is usually the case.

```

248 \def\Grtoday{%
249   \expandafter\Greeknumeral\expandafter{\the\day}\space
250   \gr@c@month \space

```

```

251 \expandafter\Greeknumeral\expandafter{\the\year}

\extrasgreek The macro \extrasgreek will perform all the extra definitions needed for the
\noextrasgreek Greek language. The macro \noextrasgreek is used to cancel the actions of
\extrasgreek. For the moment these macros switch the fontencoding (with 8-bit
TeX) and the definition of the internal macros \@alph and \@Alph because in
Greek we do use the Greek numerals.
252 \addto\extrasgreek{\greekscript}
253 \addto\noextrasgreek{\latintext}
      TODO restore previous font encoding.

\greeknumeral The command \greeknumeral needs to be fully expandable in order to get the
right information in auxiliary files. It should also be usable in PDF-strings. Therefore we use the implementation from the \HyPsd@GreekPatch in hyperref (version
7.00e 2020-05-15).
254 \def\greeknumeral#1{%
255   {\greekscript
256   \bbl@greek@GreekNum@\firstoftwo{#1}}%
257 }

\Greeknumeral The command \Greeknumeral prints uppercase greek numerals.
258 \def\Greeknumeral#1{%
259   {\greekscript
260   \bbl@greek@GreekNum@\secondoftwo{#1}}%
261 }

\bbl@greek@ill@value When the argument of \greeknumeral has a value outside of the acceptable
bounds ( $0 < x < 999999$ ) a warning will be issued (and the argument be printed).
262 \def\bbl@greek@ill@value#1{%
263   \PackageWarningNoLine{babel}{Illegal value (#1) for greeknumeral}%
264   \@arabic{#1}%
265 }

\bbl@greek@GreekNum The auxiliary macros provide the actual conversion. They are taken from hyperref
\bbl@greek@@GreekNum as well.
\bbl@greek@GreekNumI 266 \def\bbl@greek@GreekNum#1#2{%
\bbl@greek@GreekNumII 267   \ifnum#2<\@ne
\bbl@greek@GreekNumIII 268     \bbl@greek@ill@value{#2}%
\bbl@greek@GreekNumIV 269   \else
\bbl@greek@GreekNumV 270     \ifnum#2<1000000 %
\bbl@greek@GreekNumVI 271       \bbl@greek@@GreekNum#1{#2}%
272   \else
273     \bbl@greek@ill@value{#2}%
274   \fi
275 }
276 }
277 \def\bbl@greek@@GreekNum#1#2{%
278   \ifnum#2<\@m

```

```

279   \ifnum#2<10 %
280     \expandafter\bb@greek@GreekNumI
281       \expandafter\@gobble\expandafter#1\number#2%
282 \else
283   \ifnum#2<100 %
284     \expandafter\bb@greek@GreekNumII
285       \expandafter\@gobble\expandafter#1\number#2%
286 \else
287   \expandafter\bb@greek@GreekNumIII
288     \expandafter\@gobble\expandafter#1\number#2%
289   \fi
290 \fi
291 \ifnum#2>\z@%
292   \textnumeralsigngreek
293 \fi
294 \else
295   \ifnum#2<\@M
296     \expandafter\bb@greek@GreekNumIV\expandafter#1\number#2%
297 \else
298   \ifnum#2<100000 %
299     \expandafter\bb@greek@GreekNumV\expandafter#1\number#2%
300   \else
301     \expandafter\bb@greek@GreekNumVI\expandafter#1\number#2%
302   \fi
303 \fi
304 \fi
305 }
306 \def\bb@greek@GreekNumI#1#2#3{%
307   #1{%
308     \ifnum#3>\z@%
309       \textnumeralsignlowergreek
310     \fi
311   }%
312 \expandafter#2%
313 \ifcase#3 %
314   {\t@{}%
315   \or\textalpha\textAlpha
316   \or\textbeta\textBeta
317   \or\textgamma\textGamma
318   \or\textdelta\textDelta
319   \or\textepsilon\textEpsilon
320   \or\textstigmagreek\textStigmagreek
321   \or\textzeta\textZeta
322   \or\texteta\textEta
323   \or\texttheta\textTheta
324 \else
325   {\t@{}%
326 \fi
327 }
328 \def\bb@greek@GreekNumII#1#2#3#4{%

```

```

329 #1{%
330   \ifnum#3>\z@%
331     \textnumeralsignlowergreek
332   \fi
333 }%
334 \expandafter#2%
335 \ifcase#3 %
336   {}{%
337   \or\textiota\textIota
338   \or\textkappa\textKappa
339   \or\textlambda\textLambda
340   \or\textmugreek\textMu
341   \or\textnu\textNu
342   \or\textxi\textXi
343   \or\textomicron\textOmegaMicron
344   \or\textpi\textPi
345   \or\textkoppa\textKoppa
346 \else
347   {}{%
348   \fi
349 \bbbl@greek@GreekNumI#1#2#4%
350 }
351 \def\bbbl@greek@GreekNumIII#1#2#3#4#5{%
352 #1{%
353   \ifnum#3>\z@%
354     \textnumeralsignlowergreek
355   \fi
356 }%
357 \expandafter#2%
358 \ifcase#3 %
359   {}{%
360   \or\textrho\textRho
361   \or\textsigma\textSigma
362   \or\texttau\textTau
363   \or\textupsilon\textUpsilon
364   \or\textphi\textPhi
365   \or\textchi\textChi
366   \or\textpsi\textPsi
367   \or\textomega\textOmega
368   \or\text sampigreek\textSampigreek
369 \else
370   {}{%
371   \fi
372 \bbbl@greek@GreekNumII#1#2#4#5%
373 }
374 \def\bbbl@greek@GreekNumIV#1#2#3#4#5{%
375   \bbbl@greek@GreekNumI\@firstofone#1#2%
376   \bbbl@greek@@GreekNum#1{#3#4#5}%
377 }
378 \def\bbbl@greek@GreekNumV#1#2#3#4#5#6{%

```

```

379   \bb1@greek@GreekNumII\@firstofone#1#2#3%
380   \bb1@greek@@GreekNum#1{#4#5#6}%
381 }
382 \def\bb1@greek@GreekNumVI#1#2#3#4#5#6#7{%
383   \bb1@greek@GreekNumIII\@firstofone#1#2#3#4%
384   \bb1@greek@@GreekNum#1{#5#6#7}%
385 }

```

\greek@alph In the previous release of this language definition the commands `\greek@alph` and `\greek@Alpha` were kept just for reasons of compatibility. Here again they become meaningful macros. They are defined in a way that even page numbering with greek numerals is possible. Since the macros `\@alph` and `\@Alpha` will lose their original meaning while the Greek option is active, we must save their original value. macros `\@alph`

```

386 \let\latin@alph\@alph
387 \let\latin@Alpha\@Alpha

```

Then we define the Greek versions; the additional `\expandafters` are needed in order to make sure the table of contents will be correct, e.g., when we have appendixes.

```

388 \def\greek@alph#1{\expandafter\greeknumeral\expandafter{\the#1}}
389 \def\greek@Alpha#1{\expandafter\Greeknumeral\expandafter{\the#1}}

```

Now we can set up the switching.

```

390 \addto\extrasgreek{%
391   \let\@alph\greek@alph
392   \let\@Alpha\greek@Alpha}
393 \addto\noextrasgreek{%
394   \let\@alph\latin@alph
395   \let\@Alpha\latin@Alpha}

```

7 Character codes

Greek letters drop diacritics (except dialytika and sub-iota) in UPPERCASE. This is not cared for by the Unicode standard. The file `greek-euenc.def` from `greek-fontenc` contains the required `\lccode` and `\uccode` corrections from the `xgreek` package by Apostolos Syropoulos.

The LGR encoded fonts that are used to typeset Greek with 8-bit TeX define ligatures for characters with diacritics. In order for this to work, some characters need to be considered as letters. These characters are <, >, ~, ‘, ’, " and ¡. Therefore, their `\lccode` is changed when Greek is in effect. In order to let `\uppercase` give correct results, the `\uccode` of these characters is set to a non-existing character to make them disappear. Of course not all characters are needed when typesetting “modern” *μονοτονικό*. In that case we only need the ‘ and ” symbols which are treated in the proper way.

\greek@tilde The Greek script uses a number of characters with more than one accent. In LGR encoded fonts combined diacritics can be obtained using Knuth’s ligature

mechanism (see usage.pdf). Characters we need to have ligatures with are the tilde, the acute and grave accent characters, the rough and smooth breathings, the subscript, and the double quote character. In text input the ~ is normally used to produce an unbreakable space.

```

396 \@ifl@aded{def}{lgrenc}{%
397   \begingroup
398     \@ifundefined{active@char\string!}{}{\catcode`!=12\relax}
399     \catcode`\~=12%
400     \lccode`\!=`\~%
401     \lowercase{\def\x{\endgroup
402       \def\greek@tilde{!}\x}}

```

In order to get correct hyphenation we need to set the lower case code of a number of characters. The ‘v’ character has a special usage for the **cb** fonts: in fact this ligature mechanism detects the end of a word and assures that a final sigma is typeset with the proper sign which is different from that of an initial or medial sigma; the ‘v’ after an *isolated* sigma fools the ligature mechanism in order to typeset σ in place of ς . Because of this we make sure its lowercase code is not changed. For “modern” greek we have to deal only with ‘ ’ and “ ” and so things are easy. In order to process the suitable characters and in such a way that hyphenation patterns work also with precomposed characters, it is necessary to declare the lc code for all characters, that can be part of a word. We do this in **\extrasgreek** because this is a feature of the LGR font encoding (which is the same in all language variants). This means that multi-accented characters are regarded parts of a word (and not non-word characters) also in monotonic spelling.

```

403   \addto\extrasgreek{%
404     \babel@savevariable{\lccode`v}\lccode`v='v%
405     \babel@savevariable{\lccode`\'}\lccode`\'=`\%
406     \babel@savevariable{\lccode`\"}\lccode`\\"=`\%
407     % ‘high bit characters’: set in a loop and correct exceptions
408     \tempcnta=128%
409     \while{\tempcnta<253}{%
410       \expandafter\babel@savevariable\expandafter{%
411         \expandafter\lccode\the\tempcnta}%
412       \lccode\tempcnta=\tempcnta
413       \advance\tempcnta\one
414     }%
415     % Fix non-word characters:
416     \lccode151=0%
417     \lccode155=0%
418     \lccode159=0%
419     \lccode199=0%
420     % Fix capital letters:
421     \lccode195=147% GREEK LETTER DIGAMMA
422     \lccode219=240% GREEK CAPITAL LETTER IOTA WITH DIALYTIKA
423     \lccode223=244% GREEK CAPITAL LETTER UPSILON WITH DIALYTIKA
424   }
425 
```

```

426 \addto\extraspolutonikogreek{%
427   \% \l@greek=\bbl@polygreek
428   \babel@savevariable{\lccode`<`\lccode`<`%
429   \babel@savevariable{\lccode`>`\lccode`>`%
430   \babel@savevariable{\lccode`~`\lccode`~`%
431   \babel@savevariable{\lccode`|`\lccode`|`%
432   \babel@savevariable{\lccode`'`\lccode`'=`%
433 }

```

And in order to get rid of all accents and breathings when a string is \uppercased we also change a number of uppercase codes.

```

434 \addto\extrasgreek{%
435   \babel@savevariable{\uccode`"\uccode`"=``%
436   \babel@savevariable{\uccode`'}\uccode`'=159% 159 == ^9f
437 }
438 \addto\extraspolutonikogreek{%
439   \babel@savevariable{\uccode`~}\uccode`~=159%
440   \babel@savevariable{\uccode`>}\uccode`>=159%
441   \babel@savevariable{\uccode`<}\uccode`<=159%
442   \babel@savevariable{\uccode`|}\uccode`|=159%
443   \babel@savevariable{\uccode`'`\uccode`'=159%
444 }

```

For this to work we make the character ^9f a shorthand that expands to nothing. In order for this to work we need to make a character look like ^9f in TeX's eyes. The trick is to have another character and assign it a different lowercase code. To execute the macros needed in a \lowercase environment. Usually the tilde ~ character is used for such purposes. Before we do this we save it's original lowercase code to restore it once we're done.

```

445 \tempcnta=\lccode`~
446 \lccode`~=159
447 \lowercase{%
448   \initiate@active@char{~}%
449   \declare@shorthand{greek}{~}{~}%
450 \lccode`~= \tempcnta

```

Add composite commands, so that the dialytika is kept or put on the following character of a diphthong with \MakeUppercase (see lgrdef.enc from the the greek- fontenc package for details).

```

451 \DeclareTextCompositeCommand{"}{LGR}{^9f}{\accdialytika}
452 \DeclareTextCompositeCommand{'}{LGR}{^9f}{\LGR@hiatus}
453 \DeclareTextCompositeCommand{'}{LGR}{^9f}{\LGR@hiatus}

```

We can also make the tilde character itself expand to a tilde with category code 12 to make the typing of texts easier.

```

454 \addto\extraspolutonikogreek{\languageshorthands{greek}}%
455 \declare@shorthand{greek}{~}{\greek@tilde}
456 }{} % End of LGR-specific code.

```

8 symbol name aliases

For backwards compatibility, we keep aliases for a few symbols.

```
457 \providecommand*\anwtonos{\textdexiakeraia}
458 \providecommand*\katwtonos{\textaristerikeraia}
459 \providecommand*\qoppa{\textkoppa}
460 \providecommand*\varqoppa{\textqoppa}
461 \providecommand*\stigma{\textstigma}
462 \providecommand*\sampi{\textsampi}
463 \providecommand*\Digamma{\textDigamma}
464 \providecommand*\ddigamma{\textdigamma}
465 \providecommand*\vardigamma{\textvardigamma}
466 \providecommand*\euro{\texteuro}
467 \providecommand*\permill{\textperthousand}
```

TODO remove the following lines once greek-fontenc 1.0 is in common use.

```
468 \@ifl@aded{def}{lgrenc}{%
469   \ProvideTextCommand{\textKoppa}{LGR}{\textkoppa}
470   \ProvideTextCommand{\textmugreek}{LGR}{\textmu}
471 }{}%
472 \ProvideTextCommand{\textmugreek}{\greekfontencoding}{\textmu}
```

The macro `\ldf@finish` takes care of looking for a configuration file, setting the main language to be switched on at `\begin{document}` and resetting the category code of `@` to its original value.

```
473 \ldf@finish{\CurrentOption}
474 </code>
```