

Web2c

for version 2021
February 2021

Karl Berry
Olaf Weber
<https://tug.org/web2c>

This file documents the installation and use of the programs in Web2c, an implementation of Donald Knuth's TeX system.

Copyright © 1996, 1997, 1998, 1999, 2000, 2001, 2002, 2003, 2004, 2005, 2007, 2008, 2009, 2010-2021 Karl Berry & Olaf Weber.

Permission is granted to make and distribute verbatim copies of this manual provided the copyright notice and this permission notice are preserved on all copies.

Permission is granted to copy and distribute modified versions of this manual under the conditions for verbatim copying, provided that the entire resulting derived work is distributed under the terms of a permission notice identical to this one.

Permission is granted to copy and distribute translations of this manual into another language, under the above conditions for modified versions, except that this permission notice may be stated in a translation

Table of Contents

1	Introduction	1
2	Installation	2
2.1	configure options	2
2.2	Compile-time options	3
2.3	Additional targets	4
2.4	Trip, trap, and mptrap: Torture tests	4
3	Commonalities	6
3.1	Option conventions	6
3.2	Common options	6
3.3	Path searching	8
3.4	Output file location	8
4	Three programs: Metafont, MetaPost, and T_EX	10
4.1	Runtime options	10
4.2	Initial and virgin	11
4.3	Memory dumps	11
4.3.1	Creating memory dumps	11
4.3.2	Determining the memory dump to use	12
4.3.3	Hardware and memory dumps	12
4.4	Editor invocation	13
4.5	\input filenames	13
4.5.1	\input quoted filename: \input "some name"	14
4.5.2	\input braced filename: \input{some name}	14
4.5.3	\input filename caveats	14
5	T_EX: Typesetting	16
5.1	tex invocation	16
5.2	Initial T _E X	18
5.3	Formats	19
5.4	Languages and hyphenation	20
5.4.1	MLT _E X: Multi-lingual T _E X	20
5.4.1.1	\charsubdef: Character substitutions	20
5.4.1.2	\tracingcharsubdef: Substitution diagnostics	21
5.4.2	TCX files: Character translations	21
5.4.3	Patgen: Creating hyphenation patterns	23
5.5	Shell escapes	23
5.6	IPC and T _E X	24
5.7	Extended T _E X engines	24

6 Metafont: Creating typeface families	26
6.1 <code>mf</code> invocation	26
6.2 Initial Metafont	27
6.3 Modes: Device definitions for Metafont	28
6.4 Online Metafont graphics	29
6.5 GFtoDVI: Character proofs of fonts	30
6.6 MFT: Prettyprinting Metafont source	31
7 MetaPost: Generating PostScript	33
7.1 <code>mpost</code> invocation	33
7.2 Initial MetaPost	35
7.3 DVItoMP: DVI to MPX conversion	35
8 Bib_TE_X: Bibliographies	36
8.1 Bib _T E _X invocation	36
8.2 Basic Bib _T E _X style files	37
9 WEB: Literate programming	38
9.1 Tangle: Translate WEB to Pascal	38
9.2 Weave: Translate WEB to _T E _X	39
9.3 Pooltype: Display WEB pool files	39
10 DVI utilities	41
10.1 DVIconify: Canonicalize virtual font references	41
10.2 DVItypes: Plain text transliteration of DVI files	41
10.2.1 DVItypes output example	42
11 Font utilities	45
11.1 Font file formats	45
11.2 GFtoPK: Generic to packed font conversion	46
11.3 PKtoGF: Packed to generic font conversion	46
11.4 PKtype: Plain text transliteration of packed fonts	46
11.5 GFtype: Plain text transliteration of generic fonts	48
11.6 TFtoPL: _T E _X font metric to property list conversion	50
11.7 PLtoTF: Property list to _T E _X font metric conversion	52
11.8 VFtoVP: Virtual font to virtual property lists	52
11.9 VPtoVF: Virtual property lists to virtual font	53
11.10 Font utilities available elsewhere	53
Appendix A Legalisms	54
Appendix B References	55
Index	57

1 Introduction

This manual corresponds to version 2021 of Web2c, released in February 2021.

Web2c is the name of a *T_EX* implementation, originally for Unix, but now also running under various operating systems. By *T_EX implementation*, we mean all of the standard programs developed by the Stanford *T_EX* project directed by Donald E. Knuth: Metafont, DVItype, GFtoDVI, BibT_EX, Tangle, etc., as well as *T_EX* itself. Other programs are also included: DVIconf, written by Peter Breitenlohner, MetaPost and its utilities (derived from Metafont), by John Hobby, etc.

General strategy: Web2c works, as its name implies, by translating the WEB source in which *T_EX* is written into C source code. Its output is not self-contained, however; it makes extensive use of many macros and functions in a library (the `web2c/lib` directory in the sources). Therefore, it will not work without change on an arbitrary WEB program.

Availability: All of Web2c is freely available—“free” both in the sense of no cost (free ice cream) and of having the source code to modify and/or redistribute (free speech). See Section “*unixtex.ftp*” in *Kpathsea*, for the practical details of how to obtain Web2c.

Different parts of the Web2c distribution have different licensing terms, however, reflecting the different circumstances of their creation; consult each source file for exact details. The main practical implication for redistributors of Web2c is that most of the executables are covered by the GNU General Public License or GNU Lesser General Public License, and therefore anyone who gets a binary distribution must also be able to get the sources, as explained by the terms of the GPL (<https://gnu.org/licenses/>). The GPL covers the Web2c executables, including `tex`, because the Free Software Foundation sponsored the initial development of the *Kpathsea* library that Web2c uses. The basic source files from Stanford, however, have their own copyright terms or are in the public domain, and are not covered by the GPL.

History: Tomas Rokicki originated the *T_EX-to-C* system in 1987, working from the first change files for *T_EX* under Unix, which were done primarily by Howard Trickey and Pavel Curtis. Tim Morgan then took over development and maintenance for a number of years; the name changed to Web-to-C somewhere in there. In 1990, Karl Berry became the maintainer. He made many changes to the original sources, and started using the shorter name Web2c. In 1997, Olaf Weber took over, and then in 2006, Karl started taking care of it again. No significant development or changes have been needed for many years. Dozens of other people have contributed; their names are listed in the *ChangeLog* files.

Other acknowledgements by Karl: The University of Massachusetts at Boston (particularly Rick Martin and Bob Morris) provided computers and ftp access to me for many years. Richard Stallman at the Free Software Foundation employed me while I wrote the original path searching library (for the GNU font utilities). (rms also gave us Emacs, GDB, and GCC, without which I cannot imagine developing Web2c.) And, of course, *T_EX* would not exist in the first place without Donald E. Knuth.

Further reading: See Appendix B [References], page 55.

2 Installation

(A copy of this chapter is in the distribution file `web2c/INSTALL`.)

Installing Web2c is mostly the same as installing any other Kpathsea-using program. Therefore, for the basic steps involved, see Section “Installation” in *Kpathsea*. (A copy is in the file `kpathsea/INSTALL`.)

One peculiarity to Web2c is that the source distribution comes in two files: `web.tar.gz` and `web2c.tar.gz`. You must retrieve and unpack them both. (We have two because the former archive contains the very large and seldom-changing original WEB source files.) See Section “`unixtex.ftp`” in *Kpathsea*.

Another peculiarity is the MetaPost program. Although it has been installed previously as `mp`, as of Web2c 7.0 the installed name is now `mpost`, to avoid conflict with the `mp` program that does prettyprinting. This approach was recommended by the MetaPost author, John Hobby. If you as the TeX administrator wish to make it available under its shorter name as well, you will have to set up a link or some such yourself. And of course individual users can do the same.

For solutions to common installation problems and information on how to report a bug, see the file `kpathsea/BUGS` (see Section “Bugs” in *Kpathsea*). See also the Web2c home page, <http://www.tug.org/web2c>.

Points worth repeating:

- Before starting the standard compilation and installation you must install the basic fonts, macros, and other library files. See Section “Installation” in *Kpathsea*.
- If you do not wish to use the standard file locations, see Section “Changing search paths” in *Kpathsea*.
- Some Web2c features are enabled or disabled at `configure` time, as described in the first section below.

2.1 configure options

This section gives pointers to descriptions of the ‘`--with`’ and ‘`--enable`’ `configure` arguments that Web2c accepts. Some are specific to Web2c, others are generic to all Kpathsea-using programs.

For a list of all the options `configure` accepts, run ‘`configure --help`’. The generic options are listed first, and the package-specific options come last.

For a description of the generic options (which mainly allow you to specify installation directories) and basic `configure` usage, see Section “Running `configure` scripts” in *Autoconf*, a copy is in the file `kpathsea/CONFIGURE`.

`--disable-dump-share`

Do not make `fmt`/`base`/`mem` files sharable across different endian architectures.
See Section 4.3.3 [Hardware and memory dumps], page 12.

```
'--without-maketexmf-default'
'--without-maketexpk-default'
'--without-maketextfm-default'
'--with-maketextex-default'
```

Enable or disable the dynamic generation programs. See Section “mktex configuration” in *Kpathsea*. The defaults are the inverse of the options, i.e., everything is enabled except `maketex`.

```
'--enable-shared'
```

Build *Kpathsea* as a shared library. See Section “Shared library” in *Kpathsea*.

```
'--with-editor=cmd'
```

Change the default editor invoked by the ‘e’ interactive command. See Section 4.4 [Editor invocation], page 13.

```
'--with-epsfwin'
 '--with-hp2627win'
 '--with-mftalkwin'
 '--with-nextwin'
 '--with-regiswin'
 '--with-suntoolswin'
 '--with-tektronixwin'
 '--with-unitermwin'
 '--with-x'
 '--with-x-toolkit=KIT'
 '--with-x11win'
 '--with-x11'
```

Define Metafont graphics support; by default, no graphics support is enabled. See Section 6.4 [Online Metafont graphics], page 29.

```
'--x-includes=dir'
 '--x-libraries=dir'
```

Define the locations of the X11 include files and libraries; by default, `configure` does its best to guess). See Section “Optional Features” in *Autoconf*. A copy is in `kpathsea/CONFIGURE`.

2.2 Compile-time options

In addition to the `configure` options listed in the previous section, there are a few things that can be affected at compile-time with C definitions, rather than with `configure`. Using any of these is unusual.

To specify extra compiler flags ('`-Dname`' in this case), the simplest thing to do is:

```
make XCFLAGS="coptions"
```

You can also set the `CFLAGS` environment variable before running `configure`. See Section “`configure` environment” in *Kpathsea*.

Anyway, here are the possibilities:

`'-DFIXPT'`
`'-DNO_MF_ASM'`

Use the original WEB fixed-point routines for Metafont and MetaPost arithmetic calculations regarding fractions. By default, assembly-language routines are used on x86 hardware with GNU C (unless ‘`NO_MF_ASM`’ is defined), and floating-point routines are used otherwise.

`'-DIPC_DEBUG'`

Report on various interprocess communication activities. See Section 5.6 [IPC and `TeX`], page 24.

2.3 Additional targets

Web2c has several Make targets besides the standard ones. You can invoke these either in the top level directory of the source distribution (the one containing `kpathsea/` and `web2c/`), or in the `web2c/` directory.

`'c-sources'`

Make only the C files, translated from the Web sources, presumably because you want to take them to a non-Unix machine.

`'formats'`

`'install-formats'`

Make or install all the memory dumps (see Section 4.3 [Memory dumps], page 11). By default, the standard plain formats plus `latex.fmt` are made. You can add other formats by redefining the `fmts`, `bases`, and `mems` variables. See the top of `web2c/Makefile` for the possibilities.

`'fmts'`

`'install-fmts'`

Make or install the `TeX .fmt` files. See Section 5.2 [Initial `TeX`], page 18.

`'bases'`

`'install-bases'`

Make or install the Metafont `.base` files. See Section 6.2 [Initial Metafont], page 27.

`'mems'`

`'install-mems'`

Make or install the MetaPost `.mem` files. See Section 7.2 [Initial MetaPost], page 35.

`'triptrap'`

`'trip'`

`'trap'`

`'mptrap'` To run the torture tests for `TeX`, Metafont, and MetaPost (respectively). See the next section.

2.4 Trip, trap, and mptrap: Torture tests

To validate your `TeX`, Metafont, and MetaPost executables, run ‘`make triptrap`’. This runs the trip, trap, and mptrap “torture tests”. See the files `triptrap/tripman.tex`,

`triptrap/trapman.tex`, and `triptrap/mptrap.readme` for detailed information and background on the tests.

The differences between your executables' behavior and the standard values will show up on your terminal. The usual differences (these are all acceptable) are:

- string usage and table sizes;
- glue set ratios;
- ‘down4’, ‘right4’, and ‘y4’ commands in DVItype output;
- dates and times.

Any other differences are trouble. The most common culprit in the past has been compiler bugs, especially when optimizing. See Section “`TEX or Metafont failing`” in *Kpathsea*.

The files `trip.diffs`, `mftrap.diffs`, and `mptrap.diffs` in the `triptrap` directory show the standard diffs against the original output. If you diff your diffs against these files, you should come up clean. For example

```
make trip >&mytrip.diffs  
diff triptrap/trip.diffs mytrip.diffs
```

To run the tests separately, use the targets `trip`, `trap`, and `mptrap`.

To run simple tests for all the programs as well as the torture tests, run ‘`make check`’. You can compare the output to the distributed file `tests/check.log` if you like.

3 Commonalities

Many aspects of the TeX system are the same among more than one program, so we describe those pieces together, here.

3.1 Option conventions

To provide a clean and consistent behavior, we chose to have all these programs use the GNU function `getopt_long_only` to parse command lines. However, we do use in a restricted mode, where all the options have to come before the rest of the arguments.

As a result, you can:

- use ‘-’ or ‘--’ to start an option name;
- use any unambiguous abbreviation for an option name;
- separate option names and values with either ‘=’ or one or more spaces;
- use filenames that would otherwise look like options by putting them after an option ‘--’.

By convention, non-option arguments, if specified, generally define the name of an input file, as documented for each program.

If a particular option with a value is given more than once, it is the last value that counts.

For example, the following command line specifies the options ‘foo’, ‘bar’, and ‘verbose’; gives the value ‘baz’ to the ‘abc’ option, and the value ‘xyz’ to the ‘quux’ option; and specifies the filename `-myfile-`.

```
-foo --bar -verb -abc=baz -quux karl --quux xyz -- -myfile-
```

3.2 Common options

All of these programs accept the standard GNU ‘`--help`’ and ‘`--version`’ options, and several programs accept ‘`--verbose`’. Rather than writing identical descriptions for every program, they are described here.

‘`--help` Print a usage message listing basic usage and all available options to standard output, then exit successfully.

‘`--verbose`
Print progress reports to standard output.

‘`--version`
Print the version number to standard output, then exit successfully.

TeX, Metafont, and MetaPost have a number of additional options in common:

‘`-cnf-line=str`
Parse `str` as if it were a line in the `texmf.cnf` configuration file, overriding all other settings. See Section “Path searching options” in *Kpathsea*.

‘`-file-line-error`
‘`-no-file-line-error`
Change (or do not change) the way error messages are printed. The alternate style looks like error messages from many compilers and is easier

to parse for some editors that invoke TeX. This option used to be called ‘`-file-line-error-style`’.

`'-fmt=classname'`
`'-base=classname'`
`'-mem=classname'`

Use *classname* instead of the program name or a ‘%&’ line to determine the name of the memory dump file read (‘`fmt`’ for TeX, ‘`base`’ for Metafont, ‘`mem`’ for MetaPost). See Section 4.3 [Memory dumps], page 11. Also sets the program name to *classname* if no ‘`-progname`’ option was given.

`'-halt-on-error'`

Stop processing and exit when an error occurs, as opposed to the normal process of trying to recover and continue.

`'-ini'` Enable the “initial” form of the program (see Section 4.2 [Initial and virgin], page 11). This is implicitly set if the program name is `initex` resp. `inimf`.

`'-interaction=string'`

Set the interaction mode from the command line. The *string* must be one of ‘`batchmode`’, ‘`nonstopmode`’, ‘`scrollmode`’, or ‘`errorstopmode`’.

`'-jobname=string'`

Set the job name to *string*, instead of deriving it from the name of the input file.

`'-kpathsea-debug=number'`

Set path searching debugging flags according to the bits of *number* (see Section “Debugging” in *Kpathsea*). You can also specify this in `KPATHSEA_DEBUG` environment variable (for all Web2c programs). (The command line value overrides.) The most useful value is ‘`-1`’, to get all available output.

`'-output-directory dirname'`

Specify the directory *dirname* to which output files are written. Also look for input files in *dirname* first, before looking along the normal search path. See Section 3.4 [Output file location], page 8.

`'-parse-first-line'`

`'-no-parse-first-line'`

Check or disable checking whether the first line of the main input file starts with ‘%&’, and parse it if it does. This line can be used to specify the format and/or a TCX file.

`'-progname=string'`

Set program (and memory dump) name to *string*. This may affect the search paths and other values used (see Section “Config files” in *Kpathsea*). Using this option is equivalent to making a link named *string* to the binary and then invoking the binary under that name. See Section 4.3 [Memory dumps], page 11.

`'-recorder'`

Enable the filename recorder. This makes the program save a list of the opened files into a file with (by default) extension ‘`.fls`’. For Aleph, this option is always on, and the file has extension ‘`.ofl`’.

Ordinarily, the ‘.fls’ file is written to the same location as the ‘.log’ file, for example, respecting `-output-directory` if it is given (see Section 3.4 [Output file location], page 8). However, if `TEX` processing is done on the command line (or in response to the ‘**’ prompt), the ‘.fls’ might be written to the current directory, or include an integer (the current pid), as in `texput1234.fls`. You can use `-jobname` to explicitly set the basename.

`'-translate-file=tcxfile'`

Use `tcxfile` to define which characters are printable and translations between the internal and external character sets. Moreover, `tcxfile` can be explicitly declared in the first line of the main input file ‘%& `-translate-file=tcxfile`’. This is the recommended method for portability reasons. See Section 5.4.2 [TCX files], page 21.

`'-8bit'`

This option specifies that by default all characters should be considered printable. If ‘`-translate-file`’ was given as well, then the TCX file may mark characters as non-printable. This is a no-op in engines natively supporting Unicode.

3.3 Path searching

All of the Web2c programs, including `TEX`, which do path searching use the Kpathsea routines to do so. The precise names of the environment and configuration file variables which get searched for particular file formatted are therefore documented in the Kpathsea manual (see Section “Supported file formats” in *Kpathsea*). Reading `texmf.cnf` (see Section “Config files” in *Kpathsea*), invoking `mktex...` scripts (see Section “mktex scripts” in *Kpathsea*), and so on are all handled by Kpathsea.

The programs which read fonts make use of another Kpathsea feature: `texfonts.map`, which allows arbitrary aliases for the actual names of font files; for example, ‘Times-Roman’ for ‘`ptmr8r.tfm`’. The distributed (and installed by default) `texfonts.map` includes aliases for many widely available PostScript fonts by their PostScript names.

3.4 Output file location

All the programs generally follow the usual convention for output files. Namely, they are placed in the directory current when the program is run, regardless of any input file location; or, in a few cases, output is to standard output.

For example, if you run ‘`tex /tmp/foo`’, for example, the output will be in `./foo.dvi` and `./foo.log`, not `/tmp/foo.dvi` and `/tmp/foo.log`.

You can use the ‘`-output-directory`’ option to cause all output files that would normally be written in the current directory to be written in the specified directory instead. See Section 3.2 [Common options], page 6.

If the current directory is not writable, and ‘`-output-directory`’ is not specified, the main programs (`TEX`, Metafont, MetaPost, and Bib`TEX`) make an exception: if the config file or environment variable `TEXMFOUTPUT` is set (it is not by default), output files are written to the directory specified.

`TEXMFOUTPUT` is also checked for input files, as `TEX` often generates files that need to be subsequently read; for input, no suffixes (such as ‘`.tex`’) are added by default and no exhaustive path searching is done, the input name is simply checked as given.

4 Three programs: Metafont, MetaPost, and \TeX

\TeX , Metafont, and MetaPost have a number of features in common. Besides the ones here, command-line options and other commonalities are described in the previous section.

4.1 Runtime options

Besides the configure- and compile-time options described in the installation section (see Chapter 2 [Installation], page 2), you can control a number of parameters in the `texmf.cnf` runtime file read by Kpathsea (see Section “Config files” in *Kpathsea*).

The main purpose of `texmf.cnf` is to specify search paths, but array sizes and other options are also set there. Most are rather obscure. Here are a few of the more interesting values:

`'main_memory'`

Total words of memory available, for \TeX , Metafont, and MetaPost. Must remake the format file after changing.

`'extra_mem_bot'`

Extra space for “large” \TeX data structures (default 0): boxes, glue, breakpoints, et al. If you use PiCT \TeX , you may well want to set this.

`'expand_depth'`

Limit on recursive expansion calls before \TeX aborts (default 10000). If a \TeX program does an unterminated recursive expansion, \TeX will dutifully expand macros until the system’s runtime stack overflows, typically with a segmentation fault (SIGSEGV). This parameter was introduced to minimize the chance of that unpleasant (though not dangerous) crash, instead allowing \TeX to quit with a more informative message.

The crash can still happen, though, if the system has an exceptionally small memory allocation for its stack. There is no quantitative way to determine the limit, and it does not seem worth implementing system-dependent heuristics to guess at the number, since it’s highly improbable that any real \TeX code will ever need more than 10000 recursive expansions (it has never happened). For the same reason, using the `libsigsegv` library (<https://gnu.org/s/libsigsegv>) does not seem worth the effort.

`'texmf_casifold_search'`

See Section “Casing search” in *Kpathsea*.

Ideally all arrays would be dynamically expanded as necessary, so the only limiting factor would be the amount of swap space available, or some configurable limit much larger than can currently be supported.

Unfortunately, implementing this is extremely difficult, as the fixed size of arrays is assumed in many places throughout the source code. These runtime limits are a practical compromise between the compile-time limits in previous versions, and truly dynamic arrays. (On the other hand, the Web2c Bib \TeX implementation does do true dynamic reallocation of some arrays.)

Nowadays there is rarely a reason to modify the values. But if you do wish to modify `texmf.cnf`, in \TeX Live the best approach is to put your changes, and only your changes

at the top of the TL installation tree. That is, if the system `texmf.cnf` is installed in `/some/path/to/texlive/YYYY/texmf-dist/web2c/texmf.cnf` put your custom settings in `/some/path/to/texlive/YYYY/texmf.cnf`, where `YYYY` is the year of installation (if you use that subdirectory; it's the default). That way, unrelated changes to the system `texmf.cnf` can happen with normal updates, without affecting your local values.

4.2 Initial and virgin

The **T_EX** and Metafont programs each have two main variants, called *initial* and *virgin*. MetaPost no longer makes this distinction.

The initial form is enabled if:

1. the ‘-ini’ option was specified; or
2. the program name is `initex` resp. `inimf`; or
3. the first line of the main input file is ‘%&ini’;

otherwise, the virgin form is used.

The *virgin* form is the one generally invoked for production use. The first thing it does is read a memory dump (see Section 4.3.2 [Determining the memory dump to use], page 12), and then proceeds on with the main job.

The *initial* form is generally used only to create memory dumps (see the next section). It starts up more slowly than the virgin form, because it must do lengthy initializations that are encapsulated in the memory dump file.

4.3 Memory dumps

In typical use, **T_EX** and Metafont require a large number of macros to be predefined; therefore, they support *memory dump* files, which can be read much more efficiently than ordinary source code.

4.3.1 Creating memory dumps

The programs all create memory dumps in slightly idiosyncratic (thought substantially similar) way, so we describe the details in separate sections (references below). The basic idea is to run the initial version of the program (see Section 4.2 [Initial and virgin], page 11), read the source file to define the macros, and then execute the `\dump` primitive.

Also, each program uses a different filename extension for its memory dumps, since although they are completely analogous they are not interchangeable (**T_EX** cannot read a Metafont memory dump, for example).

Here is a list of filename extensions with references to examples of creating memory dumps:

T_EX (‘.fmt’) See Section 5.2 [Initial **T_EX**], page 18.

Metafont (‘.base’) See Section 6.2 [Initial Metafont], page 27.

When making memory dumps, the programs read environment variables and configuration files for path searching and other values as usual. If you are making a new installation and have environment variables pointing to an old one, for example, you will probably run into difficulties.

4.3.2 Determining the memory dump to use

The virgin form (see Section 4.2 [Initial and virgin], page 11) of each program always reads a memory dump before processing normal source input. All three programs determine the memory dump to use in the same way:

1. If the first non-option command-line argument begins with ‘&’, the program uses the remainder of that argument as the memory dump name. For example, running ‘tex \&super’ reads `super.fmt`. (The backslash protects the ‘&’ against interpretation by the shell.)
2. If the ‘-fmt’ resp. ‘-base’ option is specified, its value is used.
3. If the ‘-progname’ option is specified, its value is used.
4. If the first line of the main input file (which must be specified on the command line, not in response to ‘**’) is `%&dump`, and `dump` is an existing memory dump of the appropriate type, `dump` is used.

The first line of the main input file can also specify which character translation file is to be used: `%&-translate-file=tcxfile` (see Section 5.4.2 [TCX files], page 21).

These two roles can be combined: `%&dump -translate-file=tcxfile`. If this is done, the name of the dump must be given first.

5. Otherwise, the program uses the program invocation name, most commonly `tex` resp. `mf`. For example, if `latex` is a link to `tex`, and the user runs ‘`latex foo`’, `latex.fmt` will be used.

4.3.3 Hardware and memory dumps

By default, memory dump files are generally sharable between architectures of different types; specifically, on machines of different endianness (see Section “Byte order” in *GNU C Library*). (This is a feature of the Web2c implementation, and is not true of all TeX implementations.) If you specify ‘--disable-dump-share’ to `configure`, however, memory dumps will be endian-dependent.

The reason to do this is speed. To achieve endian-independence, the reading of memory dumps on LittleEndian architectures, such as PC’s and DEC architectures, is somewhat slowed (all the multibyte values have to be swapped). Usually, this is not noticeable, and the advantage of being able to share memory dumps across all platforms at a site far outweighs the speed loss. But if you’re installing Web2c for use on LittleEndian machines only, perhaps on a PC being used only by you, you may wish to get maximum speed.

TeXnically, even without ‘--disable-dump-share’, sharing of `.fmt` files cannot be guaranteed to work. Floating-point values are always written in native format, and hence will generally not be readable across platforms. Fortunately, TeX uses floating point only to represent glue ratios, and all common formats (plain, LATEX, AMSTEX, ...) do not do any glue setting at `.fmt`-creation time. Metafont does not use floating point in any dumped value at all.

Incidentally, different memory dump files will never compare equal byte-for-byte, because the program always dumps the current date and time. So don’t be alarmed by just a few bytes difference.

If you don’t know what endianness your machine is, and you’re curious, here is a little C program to tell you. (The `configure` script contains a similar program.) This is from the

book *C: A Reference Manual*, by Samuel P. Harbison and Guy L. Steele Jr. (see Appendix B [References], page 55).

```
main ()
{
    /* Are we little or big endian?  From Harbison&Steele.  */
    union
    {
        long l;
        char c[sizeof (long)];
    } u;
    u.l = 1;
    if (u.c[0] == 1)
        printf ("LittleEndian\n");
    else if (u.c[sizeof (long) - 1] == 1)
        printf ("BigEndian\n");
    else
        printf ("unknownEndian");

    exit (u.c[sizeof (long) - 1] == 1);
}
```

4.4 Editor invocation

\TeX , Metafont, and MetaPost all (by default) stop and ask for user intervention at an error. If the input came from a file, and the user responds with *e* or *E*, the program invokes an editor.

Specifying ‘`--with-editor=cmd`’ to `configure` sets the default editor command string to *cmd*. The environment variables/configuration values `TEXEDIT`, `MFEDIT`, and `MPEDIT` (respectively) override this. If ‘`--with-editor`’ is not specified, the default is `vi +%d %s` on Unix, and an invocation of the `TeXworks` editor on Windows. (See `texmf.cnf` for the precise values.)

In this string, ‘`%d`’ is replaced by the line number of the error, and ‘`%s`’ is replaced by the name of the current input file.

4.5 \input filenames

\TeX , Metafont, and MetaPost source programs can all read other source files with the `\input` (\TeX) and `input` (MF and MP) primitives:

```
\input name % in TeX
```

The file *name* can always be terminated with whitespace; for Metafont and MetaPost, the statement terminator ‘`;`’ also works. (\LaTeX and other macro packages provide other interfaces to `\input` that allow different notation; here we are concerned only with the primitive operation.)

As (allowed) extensions to standard \TeX , Web2c also supports specifying the filename in double quotes (“`some name`”) and in braces (`{"some name"}`), which is convenient for filenames containing spaces or other special characters, as described in the sections below.

In all cases, space tokens are ignored after the filename is read.

Also, double quote ("") characters are ignored within the filename; there is no way to read files whose names contain a "".

However, for maximal portability of your document across systems, use only the characters ‘a’–‘z’, ‘0’–‘9’, and at most one ‘.’. Do not use anything but simple filenames, since directory separators vary among systems; instead, add the necessary directories to the appropriate search path.

4.5.1 \input quoted filename: \input "some name"

As of Web2c version 7.5.3 (2004), double-quote characters can be used to include spaces or other special characters. In typical use, the “” characters surround the entire filename:

```
\input "filename with spaces"
```

Technically, the quote characters can be used inside the name, and can enclose any characters, as in:

```
\input filename" "with" "spaces
```

One more point. In L^AT_EX, the quotes are needed inside the braces of its \input macro, thus:

```
\input{a b}      % fails
\input{"a b"}   % ok
```

There is no way to quote the quote character.

4.5.2 \input braced filename: \input{some name}

As of Web2c 2020, \input filenames in TeX engines (this does not apply in Metafont and MetaPost) can also be specified within a TeX group, typically curly braces. For example:

```
\input{filename with spaces}
```

As always with TeX, the brace characters are not hardwired; what counts is the category code: the first token after the \input must be of catcode 1 (begin group), and it is matched with the next character of catcode 2 (end group).

Within the group-delimited filename, braces are treated as normal characters.

As with all forms of filenames, following spaces are ignored (after the end group), and double quote (") characters are ignored within the filename.

4.5.3 \input filename caveats

The quoting mechanisms just described come into play *after* TeX has tokenized and expanded the input. So, multiple spaces and tabs will generally be seen as a single space, active characters such as ‘~’ are expanded first (generally causing an error), and so on. More examples below.

On the other hand, various C library routines and Unix itself use the null byte (character code zero, ASCII NUL) to terminate strings. So filenames in Web2c cannot contain nulls, even though TeX itself does not treat NUL specially.

Finally, the present Web2c implementation does ‘~’ and ‘\$’ expansion on *name*, unlike Knuth’s original implementation. Thus:

```
\input ~jsmith/$foo.bar
```

will dereference the environment variable or Kpathsea config file value ‘`foo`’ and read that file, extended with ‘`.bar`’, in user ‘`jsmith`’s home directory. You can also use braces in the variable expansion, as in ‘ `${foo}bar`’, if you want to follow the variable name with a letter, numeral, or ‘`_`’.

(So another way to get a program to read a filename containing whitespace is to define an environment variable and dereference it.)

In all the common TeX formats (plain TeX, L^AT_EX, ConTeXt, AMSTeX, . . .), the characters ‘`~`’ and ‘`$`’ have special category codes, so to actually use these in a document you have to change their catcodes or use `\string`.

5 T_EX: Typesetting

T_EX is a typesetting system: it was especially designed to handle complex mathematics, as well as most ordinary text typesetting.

T_EX is a batch language, like C or Pascal, and not an interactive “word processor”: you compile a T_EX input file into a corresponding device-independent (DVI) file (and then translate the DVI file to the commands for a particular output device). This approach has both considerable disadvantages and considerable advantages. For a complete description of the T_EX language, see *The T_EXbook* (see Appendix B [References], page 55). Many other books on T_EX, introductory and otherwise, are available.

5.1 tex invocation

T_EX (usually invoked as `tex`) formats the given text and commands, and outputs a corresponding device-independent representation of the typeset document. This section merely describes the options available in the Web2c implementation. For a complete description of the T_EX typesetting language, see *The T_EXbook* (see Appendix B [References], page 55).

T_EX, Metafont, and MetaPost process the command line (described here) and determine their memory dump (`fmt`) file in the same way (see Section 4.3 [Memory dumps], page 11). Synopses:

```
tex [option]... [texname[.tex]] [tex-commands]
tex [option]... \first-line
tex [option]... &fmt args
```

T_EX searches the usual places for the main input file `texname` (see Section “Supported file formats” in *Kpathsea*), extending `texname` with `.tex` if necessary. To see all the relevant paths, set the environment variable `KPATHSEA_DEBUG` to ‘-1’ before running the program.

After `texname` is read, T_EX processes any remaining `tex-commands` on the command line as regular T_EX input. Also, if the first non-option argument begins with a T_EX escape character (usually `\`), T_EX processes all non-option command-line arguments as a line of regular T_EX input.

If no arguments or options are specified, T_EX prompts for an input file name with ‘**’.

T_EX writes the main DVI output to the file `basetexname.dvi`, where `basetexname` is the basename of `texname`, or ‘`texput`’ if no input file was specified. A DVI file is a device-independent binary representation of your T_EX document. The idea is that after running T_EX, you translate the DVI file using a separate program to the commands for a particular output device, such as a PostScript printer (see Section “Introduction” in *Dvips*) or an X Window System display (see *xvvi(1)*).

T_EX also reads TFM files for any fonts you load in your document with the `\font` primitive. By default, it runs an external program named `mktexpf` to create any nonexistent TFM files. You can disable this at configure-time or runtime (see Section “mktex configuration” in *Kpathsea*). This is enabled mostly for the sake of the EC fonts, which can be generated at any size.

T_EX can write output files, via the `\openout` primitive; this opens a security hole vulnerable to Trojan horse attack: an unwitting user could run a T_EX program that overwrites, say, `~/.rhosts`. (MetaPost has a `write` primitive with similar implications). To alleviate

this and similar problems the functions `kpathsea_out_name_ok` and `kpathsea_in_name_ok` from the Kpathse library (see Section “Calling sequence” in *Kpathsea*) are used to determine if a given filename is acceptable to be opened for output or input, depending on the setting of the configuration variables `openout_any` and `openin_any`: ‘a’ (for “any”, the default for `openin_any`), ‘r’ (for “restricted”), or ‘p’ (for “paranoid”, the default for `openout_any`).

In any case, all `\openout` filenames are recorded in the log file, except those opened on the first line of input, which is processed when the log file has not yet been opened.

The program accepts the following options, as well as the standard ‘-help’ and ‘-version’ (see Section 3.2 [Common options], page 6):

- ‘-enc’
- ‘-[no]-file-line-error’
- ‘-fmt=*fmtname*’
- ‘-halt-on-error’
- ‘-ini’
- ‘-interaction=*string*’
- ‘-ipc’
- ‘-ipc-start’
- ‘-jobname=*string*’
- ‘-kpathsea-debug=*number*’
- ‘-[no]parse-first-line’
- ‘-output-directory’
- ‘-progname=*string*’
- ‘-recorder’
- ‘-translate-file=*tcxfile*’
- ‘-8bit’ These options are common to T_EX, Metafont, and MetaPost. See Section 3.2 [Common options], page 6.
- ‘-enc’ Enable encT_EX extensions, such as `\mubyte`. This can be used to support the Unicode UTF-8 input encoding, although using an engine with native Unicode support is more common nowadays. <http://www.olsak.net/enctex.html>.
- ‘-ipc’
- ‘-ipc-start’

With either option, T_EX writes its DVI output to a socket as well as to the usual `.dvi` file. With ‘-ipc-start’, T_EX also opens a server program at the other end to read the output. See Section 5.6 [IPC and T_EX], page 24.

These options are available only if the ‘--enable-ipc’ option was specified to `configure` during installation of Web2c.

- ‘-mktex=*filetype*’
- ‘-no-mktex=*filetype*’
- Turn on or off the ‘`mktex`’ script associated with *filetype*. For T_EX proper, *filetype* can only be ‘tex’ and ‘tfm’, but for pdfT_EX and luaT_EX, it can also be ‘pk’.
- ‘-mltex’ If we are INITEX (see Section 4.2 [Initial and virgin], page 11), enable MLT_EX extensions such as `\charsubdef`. Implicitly set if the program name is `mltex`. See Section 5.4.1 [MLT_EX], page 20.

`'-output-comment=string'`

Use *string* as the DVI file comment. Ordinarily, this comment records the date and time of the T_EX run, but if you are doing regression testing, you may not want the DVI file to have this spurious difference. This is also taken from the environment variable and config file value ‘`output_comment`’.

`'-shell-escape'`

`'-no-shell-escape'`

`'-shell-restricted'`

Enable, or disable, or enable with restrictions the `\write18{shell-command}` feature for external executing shell commands. See Section 5.5 [Shell escapes], page 23.

`'-enable-write18'`

`'-disable-write18'`

Synonyms for `-shell-escape` and `-no-shell-escape`, for compatibility with MiK_TE_X. (MiK_TE_X also accepts both pairs of options.) See Section 5.5 [Shell escapes], page 23.

`'-src-specials'`

`'-src-specials=string'`

This option makes T_EX output specific source information using ‘`\special`’ commands in the DVI file. These ‘`\special`’ track the current file name and line number.

Using the first form of this option, the ‘`\special`’ commands are inserted automatically.

In the second form of the option, *string* is a comma separated list of the following values: ‘`cr`’, ‘`display`’, ‘`hbox`’, ‘`math`’, ‘`par`’, ‘`parend`’, ‘`vbox`’. You can use this list to specify where you want T_EX to output such commands. For example, ‘`-src-specials=cr,math`’ will output source information every line and every math formula.

These commands can be used with the appropriate DVI viewer and text editor to switch from the current position in the editor to the same position in the viewer and back from the viewer to the editor.

This option works by inserting ‘`\special`’ commands into the token stream, and thus in principle these additional tokens can be recovered or seen by the tricky-enough macros. If you run across a case, let us know, because this counts as a bug. However, such bugs are very hard to fix, requiring significant changes to T_EX, so please don’t count on it.

Redefining ‘`\special`’ will not affect the functioning of this option. The commands inserted into the token stream are hard-coded to always use the ‘`\special`’ primitive.

T_EX does not pass the trip test when this option is enabled.

5.2 Initial T_EX

The *initial* form of T_EX is invoked by ‘`tex -ini`’. It does lengthy initializations avoided by the “virgin” (`vir`) form, so as to be capable of dumping ‘`.fmt`’ files (see Section 4.3

[Memory dumps], page 11). For a detailed comparison of virgin and initial forms, see Section 4.2 [Initial and virgin], page 11.

For a list of options and other information, see Section 5.1 [tex invocation], page 16.

Unlike Metafont and MetaPost, many format files are commonly used with T_EX. The standard one implementing the features described in the *T_EXbook* is ‘plain.fmt’, also known as ‘tex.fmt’ (again, see Section 4.3 [Memory dumps], page 11). It is created by default during installation, but you can also do so by hand if necessary (e.g., if an update to plain.tex is issued):

```
tex -ini '\input plain \dump'
```

(The quotes prevent interpretation of the backslashes from the shell.) Then install the resulting plain.fmt in ‘\$(fmdir)’ (/usr/local/share/texmf/web2c by default), and link tex.fmt to it.

The necessary invocation for generating a format file differs for each format, so instructions that come with the format should explain. The top-level web2c Makefile has targets for making most common formats: plain latex amstex texinfo eplain. See Section 5.3 [Formats], page 19, for more details on T_EX formats.

5.3 Formats

T_EX *formats* are large collections of macros, often dumped into a .fmt file (see Section 4.3 [Memory dumps], page 11) by tex -ini (see Section 5.2 [Initial TeX], page 18). A number of formats are in reasonably widespread use, and the Web2c Makefile has targets to make the versions current at the time of release. You can change which formats are automatically built by setting the fmts Make variable; by default, only the ‘plain’ and ‘latex’ formats are made.

Nowadays, the formats are generally installed and updated as part of a larger T_EX distribution, such as T_EX Live (<https://tug.org/texlive>).

latex	The most widely used format. The current release is named ‘L ^A T _E X2e’; new versions are released approximately every six months, with patches issued as needed. The old release was called ‘L ^A T _E X 2.09’, and is no longer maintained or supported. L ^A T _E X attempts to provide generic markup instructions, such as “emphasize”, instead of specific typesetting instructions, such as “use the 10 pt Computer Modern italic font”. The L ^A T _E X home page: https://www.latex-project.org .
context	ConT _E Xt is an independent macro package which has a basic document structuring approach similar to L ^A T _E X. It also supports creating interactive PDF files and has integrated MetaPost support, among many other interesting features. The ConT _E Xt home page: http://www.pragma-ade.com .
amstex	The official typesetting system of the American Mathematical Society. Like L ^A T _E X, it encourages generic markup commands. The AMS also provides many L ^A T _E X packages for authors who prefer L ^A T _E X. Taken together, they are used to produce nearly all AMS publications, e.g., <i>Mathematical Reviews</i> . The AMST _E X home page: https://www.ams.org/tex .
texinfo	The documentation system developed and maintained by the Free Software Foundation for their software manuals. It can be automatically converted into

plain text, a machine-readable on-line format called ‘info’, HTML, etc. The Texinfo home page: <https://www.gnu.org/software/texinfo>.

- eplain** The “expanded plain” format provides various common features (e.g., symbolic cross-referencing, tables of contents, indexing, citations using BibT_EX), for those authors who prefer to handle their own high-level formatting. The Eplain home page: <https://tug.org/eplain>.
- slitex** An obsolete L^AT_EX 2.09 format for making slides. It is replaced by the ‘slides’ document class, although the ‘beamer’ package is the most commonly method for making slides nowadays. The Beamer page on CTAN: <https://ctan.org/pkg/beamer>.

5.4 Languages and hyphenation

T_EX supports most natural languages. See also Section 5.7 [T_EX extensions], page 24.

5.4.1 MLT_EX: Multi-lingual T_EX

Multi-lingual T_EX (`mltex`) is an extension of T_EX originally written by Michael Ferguson and now updated and maintained by Bernd Raichle. With the advent of Unicode, it has become obsolete, though it is still supported in Web2c in the event of bugs or compilation bugs.

MLT_EX allows the use of non-existing glyphs in a font by declaring glyph substitutions. These are restricted to substitutions of an accented character glyph, which need not be defined in the current font, by its appropriate `\accent` construction using a base and accent character glyph, which do have to exist in the current font. This substitution is automatically done behind the scenes, if necessary, and thus MLT_EX additionally supports hyphenation of words containing an accented character glyph for fonts missing this glyph (e.g., Computer Modern). Standard T_EX suppresses hyphenation in this case.

MLT_EX works at .fmt-creation time: the basic idea is to specify the ‘`-mltex`’ option to T_EX when you `\dump` a format. Then, when you subsequently invoke T_EX and read that .fmt file, the MLT_EX features described below will be enabled.

Generally, you use special macro files to create an MLT_EX .fmt file.

The sections below describe the two new primitives that MLT_EX defines. Aside from these, MLT_EX is completely compatible with standard T_EX.

5.4.1.1 `\charsubdef`: Character substitutions

The most important primitive MLT_EX adds is `\charsubdef`, used in a way reminiscent of `\chardef`:

```
\charsubdef composite [=] accent base
```

Each of *composite*, *accent*, and *base* are font glyph numbers, expressed in the usual T_EX syntax: ‘`\e` symbolically, ’145 for octal, ”65 for hex, 101 for decimal.

MLT_EX’s `\charsubdef` declares how to construct an accented character glyph (not necessarily existing in the current font) using two character glyphs (that do exist). Thus it defines whether a character glyph code, either typed as a single character or using the `\char` primitive, will be mapped to a font glyph or to an `\accent` glyph construction.

For example, if you assume glyph code 138 (decimal) for an e-circumflex (ê) and you are using the Computer Modern fonts, which have the circumflex accent in position 18 and lowercase ‘e’ in the usual ASCII position 101 decimal, you would use `\charsubdef` as follows:

```
\charsubdef 138 = 18 101
```

For the plain T_EX format to make use of this substitution, you have to redefine the circumflex accent macro `\^` in such a way that if its argument is character ‘e’ the expansion `\char138` is used instead of `\accent18 e`. Similar `\charsubdef` declaration and macro redefinitions have to be done for all other accented characters.

To disable a previous `\charsubdef c`, redefine `c` as a pair of zeros. For example:

```
\charsubdef '321 = 0 0 % disable N tilde
```

(Octal ’321 is the ISO Latin-1 value for the Spanish N tilde.)

`\charsubdef` commands should only be given once. Although in principle you can use `\charsubdef` at any time, the result is unspecified. If `\charsubdef` declarations are changed, usually either incorrect character dimensions will be used or MLT_EX will output missing character warnings. (The substitution of a `\charsubdef` is used by T_EX when appending the character node to the current horizontal list, to compute the width of a horizontal box when the box gets packed, and when building the `\accent` construction at `\shipout`-time. In summary, the substitution is accessed often, so changing it is not desirable, nor generally useful.)

5.4.1.2 \tracingcharsubdef: Substitution diagnostics

To help diagnose problems with ‘`\charsubdef`’, MLT_EX provides a new primitive parameter, `\tracingcharsubdef`. If positive, every use of `\charsubdef` will be reported. This can help track down when a character is redefined.

In addition, if the T_EX parameter `\tracinglostchars` is 100 or more, the character substitutions actually performed at `\shipout`-time will be recorded.

5.4.2 TCX files: Character translations

TCX (T_EX character translation) files help T_EX support direct input of 8-bit international characters if fonts containing those characters are being used. Specifically, they map an input (keyboard) character code to the internal T_EX character code (a superset of ASCII).

Of the various proposals for handling more than one input encoding, TCX files were chosen because they follow Knuth’s original ideas for the use of the ‘`xchr`’ and ‘`xord`’ tables. He ventured that these would be changed in the WEB source in order to adjust the actual version to a given environment. It turns out, however, that recompiling the WEB sources is not as simple a task as Knuth may have imagined; therefore, TCX files, providing the possibility of changing of the conversion tables on on-the-fly, have been implemented instead.

This approach limits the portability of T_EX documents, as some implementations do not support it (or use a different method for input-internal reencoding). It may also be problematic to determine the encoding to use for a T_EX document of unknown provenance; in the worst case, failure to do so correctly may result in subtle errors in the typeset output. But we feel the benefits outweigh these disadvantages.

This is entirely independent of the MLT_EX extension (see Section 5.4.1 [MLT_EX], page 20): whereas a TCX file defines how an input keyboard character is mapped to T_EX’s internal code, MLT_EX defines substitutions for a non-existing character glyph in a font with a \accent construction made out of two separate character glyphs. TCX files involve no new primitives; it is not possible to specify that an input (keyboard) character maps to more than one character.

Information on specifying TCX files:

- The best way to specify a TCX file is to list it explicitly in the first line of the main document:

```
%& -translate-file=tcxfile
```

- You can also specify a TCX file to be used on a particular T_EX run with the command-line option ‘-translate-file=tcxfile’.
- TCX files are searched for along the WEB2C path.
- Initial T_EX (see Section 5.2 [Initial T_EX], page 18) ignores TCX files.

The Web2c distribution comes with a number of TCX files. Two important ones are `i11-t1.tcx` and `i12-t1.tcx`, which support ISO Latin 1 and ISO Latin 2, respectively, with Cork-encoded fonts (a.k.a. the L^AT_EX T1 encoding). TCX files for Czech, Polish, and Slovak are also provided.

One other notable TCX file is `empty.tcx`, which is, well, empty. Its purpose is to reset Web2C’s behavior to the default (only visible ASCII being printable, as described below) when a format was dumped with another TCX being active—which is in fact the case for everything but plain T_EX in the TeX Live and other distributions. Thus:

```
latex somefile8.tex
⇒ terminal etc. output with 8-bit chars
latex --translate-file=empty.tcx somefile8.tex
⇒ terminal etc. output with ^~ notation
```

Syntax of TCX files:

1. Line-oriented. Blank lines are ignored.
2. Whitespace is ignored except as a separator.
3. Comments start with ‘%’ and continue to the end of the line.
4. Otherwise, a line consists of one or two character codes, optionally followed by 0 or 1. The last number indicates whether *dest* is considered printable.

```
src [dest [prnt]]
```

5. Each character code may be specified in octal with a leading ‘0’, hexadecimal with a leading ‘0x’, or decimal otherwise. Values must be between 0 and 255, inclusive (decimal).
6. If the *dest* code is not specified, it is taken to be the same as *src*.
7. If the same *src* code is specified more than once, it is the last definition that counts.

Finally, here’s what happens: when T_EX sees an input character with code *src*, it 1) changes *src* to *dest*; and 2) makes the *dest* code “printable”, i.e., printed as-is in diagnostics and the log file rather than in ‘^~’ notation.

By default, no characters are translated, and character codes between 32 and 126 inclusive (decimal) are printable.

Specifying translations for the printable ASCII characters (codes 32–127) will yield unpredictable results. Additionally you shouldn't make the following characters printable: `^I` (TAB), `^J` (line feed), `^M` (carriage return), and `^?` (delete), since TeX uses them in various ways.

Thus, the idea is to specify the input (keyboard) character code for `src`, and the output (font) character code for `dest`.

By default, only the printable ASCII characters are considered printable by TeX. If you specify the '`-8bit`' option, all characters are considered printable by default. If you specify both the '`-8bit`' option and a TCX file, then the TCX can set specific characters to be non-printable.

Both the specified TCX encoding and whether characters are printable are saved in the dump files (like `tex.fmt`). So by giving these options in combination with '`-ini`', you control the defaults seen by anyone who uses the resulting dump file.

When loading a dump, if the '`-8bit`' option was given, then all characters become printable by default.

When loading a dump, if a TCX file was specified, then the TCX data from the dump is ignored and the data from the file used instead.

5.4.3 Patgen: Creating hyphenation patterns

Patgen creates hyphenation patterns from dictionary files for use with TeX. Synopsis:

```
patgen dictionary patterns output translate
```

Each argument is a filename. No path searching is done. The output is written to the file `output`.

In addition, Patgen prompts interactively for other values.

For more information, see *Word hyphen-a-tion by com-puter* by Frank Liang (see Appendix B [References], page 55), and also the `patgen.web` source file.

The only options are '`-help`' and '`-version`' (see Section 3.2 [Common options], page 6).

5.5 Shell escapes

TeX can execute *shell escapes*, that is, arbitrary shell commands. Although tremendously useful, this also has obvious security implications. Therefore, as of TeX Live 2009, a *restricted* mode for shell escapes is the default mode of operation, which allows executing only certain commands, as specified in the `texmf.cnf` configuration file.

- Unrestricted shell escapes are allowed if the option `--shell-escape` is specified, or if the environment variable or config file value `shell_escape` is set to '`t`' or '`y`' and '`1`'.
- Restricted shell escapes are allowed if `shell_escape` is set to '`p`'. This is the default.
- Shell escapes are completely disabled if `--no-shell-escape` is specified, or if `shell_escape` is set to anything else.

When enabled, the TeX construct to execute a system command is `\write18{shell-command}`; for example:

```
\write18{echo "hello, world"}
```

From T_EX's point of view, this is a normal `\write` command, and is therefore subject to the usual T_EX expansions. Also, the system call either happens during the '`\output`' routine or right away, according to the absence or presence of the `\immediate` prefix, as usual for `\write`.

The *shell-command* string is passed to the command shell (via the C library function `system`). The output of *shell-command* is not diverted anywhere, so it will not appear in the log file, or anywhere but the terminal output. The exit status of the system call is also not available to T_EX.

In unrestricted mode, the argument is simply passed straight to `system` unaltered.

In restricted mode, ASCII double quote characters ("") should always be used in the argument to `\write18` where quoting of arguments is needed, as in the example above. This is to achieve some measure of system independence. On Unix systems, these are replaced with single quote (') characters to avoid insecure further expansion. Care is also taken on Windows to avoid additional expansions (from, e.g., '...'). Mismatched quotation marks in the command string result in a diagnostic message in the log file; no execution is performed.

After quotation processing, if the first word (delimited by a space or tab) of the command is in the list specified by the `shell_escape_commands` configuration value, the command is executed. Otherwise it is not. In any case, a message is written to the log file.

The `shell_escape_commands` value is a comma-separated list of words. Whitespace is significant, and typically should not be present. The default definition in `texmf.cnf` looks like this, but with more commands included:

```
shell_escape_commands = bibtex,kpsewhich,repstopdf,...
```

pdfT_EX and luaT_EX support reading (via `\input` and `\openin`) and writing (via `\openout`) from pipes if the first character is '|'. The following command is then treated exactly the same as the argument to `\write18`. In these engines, the primitive variable `\pdfshellescape` is set to 0 if shell escapes are disabled, 1 if they are enabled, and 2 if they are enabled with restrictions.

The purpose of this feature is to make it possible for T_EX documents to perform useful external actions in the common case of an individual user running a known document on his or her own machine. In such environments as CGI scripts or wikis where the input has to be considered untrustworthy, shell escapes should be completely disabled.

5.6 IPC and T_EX

(If anyone uses this feature and needs documentation, write `tex-k@tug.org`.)

This functionality is available only if the '--enable-ipc' option was specified to `configure` during installation of Web2c (see Chapter 2 [Installation], page 2).

If you define `IPC_DEBUG` before compilation (e.g., with 'make XCFLAGS=-DIPC_DEBUG'), T_EX will print messages to standard error about its socket operations. This may be helpful if you are, well, debugging.

5.7 Extended T_EX engines

The base T_EX program has been extended in many ways. Here's a partial list.

e-T _E X	Adds many new primitives, including right-to-left typesetting and more registers. Now frozen. More info: https://ctan.org/pkg/etex .
Aleph	This adds Unicode support, right-to-left typesetting, and more. Omega was the original program. Aleph is an updated version with a variety of bug fixes, and includes e-T _E X. Aleph is not actively maintained. More info: https://ctan.org/pkg/aleph , https://ctan.org/pkg/omega .
pdfT _E X	Can produce PDF as well as DVI files. It also incorporates the e-T _E X extensions, new primitives for hypertext and micro-typography, reading/writing from pipes, and much more. In T _E X Live, the command <code>etex</code> invokes pdfT _E X to make all these additions available with DVI output. Home page: http://pdftex.org .
LuaT _E X	Embeds the Lua programming language (http://lua.org) and opens up the T _E X typesetting engine to control from Lua, starting from the pdfT _E X capabilities as a base. Also natively supports UTF-8 input, the OpenType and TrueType font formats, and use of system fonts. Home page: http://luatex.org .
XeT _E X	Combines support for Unicode input, the OpenType and TrueType font formats, and use of system fonts with the capabilities of pdfT _E X, with the exception of the font expansion part of micro-typography. Home page: https://tug.org/xetex .
pT _E X upT _E X	With additional support for Japanese; pT _E X was the original engine, and upT _E X has native Unicode support and thus is more useful for Chinese and Korean. More info: https://ctan.org/pkg/ptex , https://ctan.org/pkg/uptex .
epT _E X eupT _E X	Further extends pT _E X and upT _E X with the e-T _E X extensions. More info: https://ctan.org/pkg/eptex , https://ctan.org/pkg/euptex .

6 Metafont: Creating typeface families

Metafont is a system for producing shapes; it was designed for producing complete typeface families, but it can also produce geometric designs, dingbats, etc. And it has considerable mathematical and equation-solving capabilities which can be useful entirely on their own.

Metafont is a batch language, like C or Pascal: you compile a Metafont program into a corresponding font, rather than interactively drawing lines or curves. This approach has both considerable disadvantages (people unfamiliar with conventional programming languages will be unlikely to find it usable) and considerable advantages (you can make your design intentions specific and parameterizable). For a complete description of the Metafont language, see *The METAFONTbook* (see Appendix B [References], page 55).

6.1 mf invocation

Metafont (usually invoked as `mf`) reads character definitions specified in the Metafont programming language, and outputs the corresponding font. This section merely describes the options available in the Web2c implementation. For a complete description of the Metafont language, see *The Metafontbook* (see Appendix B [References], page 55).

Metafont processes its command line and determines its memory dump (base) file in a way exactly analogous to MetaPost and TeX (see Section 5.1 [tex invocation], page 16, and see Section 4.3 [Memory dumps], page 11). Synopses:

```
mf [option]... [mfname[.mf]] [mf-commands]
mf [option]... \first-line
mf [option]... &base args
```

Most commonly, a Metafont invocation looks like this:

```
mf '\mode:=mode; mag:=magnification; input mfname'
```

(The single quotes avoid unwanted interpretation by the shell.)

Metafont searches the usual places for the main input file *mfname* (see Section “Supported file formats” in *Kpathsea*), extending *mfname* with `.mf` if necessary. To see all the relevant paths, set the environment variable `KPATHSEA_DEBUG` to ‘`-1`’ before running the program. By default, Metafont runs an external program named `mktexmf` to create any nonexistent Metafont source files you input. You can disable this at configure-time or run-time (see Section “mktex configuration” in *Kpathsea*). This is mostly for the sake of the EC fonts, which can be generated at any size.

Metafont writes the main GF output to the file `basemfname.nnngf`, where *nnn* is the font resolution in pixels per inch, and *basemfname* is the basename of *mfname*, or ‘`mfput`’ if no input file was specified. A GF file contains bitmaps of the actual character shapes. Usually GF files are converted immediately to PK files with GFtoPK (see Section 11.2 [gftopk invocation], page 46), since PK files contain equivalent information, but are more compact. (Metafont output in GF format rather than PK for only historical reasons.)

Metafont also usually writes a metric file in TFM format to `basemfname.tfm`. A TFM file contains character dimensions, kerns, and ligatures, and spacing parameters. TeX reads only this `.tfm` file, not the GF file.

The *mode* in the example command above is a name referring to a device definition (see Section 6.3 [Modes], page 28); for example, `localfont` or `ljfour`. These device definitions

must generally be precompiled into the base file. If you leave this out, the default is **proof** mode, as stated in *The Metafontbook*, in which Metafont outputs at a resolution of 2602 dpi; this is usually not what you want. The remedy is simply to assign a different mode—**localfont**, for example.

The *magnification* assignment in the example command above is a magnification factor; for example, if the device is 600 dpi and you specify **mag:=2**, Metafont will produce output at 1200 dpi. Very often, the *magnification* is an expression such as **magstep(.5)**, corresponding to a TeX “magstep”, which are factors of $1.2\sqrt{2}$.

After running Metafont, you can use the font in a TeX document as usual. For example:

```
\font\myfont = newfont
\myfont Now I am typesetting in my new font (minimum hamburgers).
```

The program accepts the following options, as well as the standard ‘-help’ and ‘-version’ (see Section 3.2 [Common options], page 6):

```
'-[no]-file-line-error'
'-fmt=fmtname'
'-halt-on-error'
'-ini'
'-interaction=string'
'-jobname=string'
'-kpathsea-debug=number'
'-[no]parse-first-line'
'-output-directory'
'-progname=string'
'-recorder'
'-translate-file=texfile'
'-8bit' These options are common to TeX, Metafont, and MetaPost. See Section 3.2
[Common options], page 6.

'-mktex=filetype'
'-no-mktex=filetype'
```

Turn on or off the ‘**mktex**’ script associated with *filetype*. The only value that makes sense for *filetype* is ‘**mf**’.

6.2 Initial Metafont

inimf is the “initial” form of Metafont, which does lengthy initializations avoided by the “virgin” (**vir**) form, so as to be capable of dumping ‘.base’ files (see Section 4.3 [Memory dumps], page 11). For a detailed comparison of virgin and initial forms, see Section 4.2 [Initial and virgin], page 11.

For a list of options and other information, see Section 6.1 [mf invocation], page 26.

The only memory dump file commonly used with Metafont is the default ‘**plain.base**’, also known as ‘**mf.base**’ (again, see Section 4.3 [Memory dumps], page 11). It is created by default during installation, but you can also do so by hand if necessary (e.g., if a Metafont update is issued):

```
mf -ini '\input plain; input modes; dump'
```

(The quotes prevent interpretation of the backslashes from the shell.) Then install the resulting `plain.base` in `'$(basedir)'` (`/usr/local/share/texmf/web2c` by default), and link `mf.base` to it.

For an explanation of the additional `modes.mf` file, see Section 6.3 [Modes], page 28. This file has no counterpart in T_EX or MetaPost.

In the past, it was sometimes useful to create a base file `cmmf.base` (a.k.a. `cm.base`), with the Computer Modern macros also included in the base file. Nowadays, however, the additional time required to read `cmbase.mf` is exceedingly small, usually not enough to be worth the administrative hassle of updating the `cmmf.base` file when you install a new version of `modes.mf`. People actually working on a typeface may still find it worthwhile to create their own base file, of course.

6.3 Modes: Device definitions for Metafont

Running Metafont and creating Metafont base files requires information that T_EX and MetaPost do not: *mode* definitions which specify device characteristics, so Metafont can properly rasterize the shapes.

When making a base file, a file containing modes for locally-available devices should be input after `plain.mf`. One commonly used file is `ftp://ftp.tug.org/tex/modes.mf`; it includes all known definitions.

If, however, for some reason you have decreased the memory available in your Metafont, you may need to copy `modes.mf` and remove the definitions irrelevant to you (probably most of them) instead of using it directly. (Or, if you're a Metafont hacker, maybe you can suggest a way to redefine `mode_def` and/or `mode_setup`; right now, the amount of memory used is approximately four times the total length of the `mode_def` names, and that's a lot.)

If you have a device not included in `modes.mf`, please see comments in that file for how to create the new definition, and please send the definition to `tex-fonts@math.utah.edu` to get it included in the next release of `modes.mf`.

Usually, when you run Metafont you must supply the name of a mode that was dumped in the base file. But you can also define the mode characteristics dynamically, by invoking Metafont with an assignment to `smode` instead of `mode`, like this:

```
mf '\smode:="newmode.mf"; mag:=magnification; input mfname'
```

This is most useful when you are working on the definition of a new mode.

The *magnification* and *mfname* arguments are explained in Section 6.1 [mf invocation], page 26. In the file `newmode.mf`, you should have the following (with no `mode_def` or `enddef`), if you are using `modes.mf` conventions:

```
mode_param (pixels_per_inch, dpi);
mode_param (blacker, b);
mode_param (fillin, f);
mode_param (o_correction, o);
mode_common_setup_;
```

(Of course, you should use real numbers for *dpi*, *b*, *f*, and *o*.)

For more information on the use of `smode`, or if you are not using `modes.mf`, see page 269 of *The Metafontbook*.

6.4 Online Metafont graphics

The Web2c implementation of Metafont can do online graphics with a number of devices. (See the Metafont manual for more information about how to draw on your screen.) By default, no graphics support is enabled.

Metafont examines the `MFTERM` environment variable or config file value at runtime, or the `TERM` environment variable if `MFTERM` is not set, to determine the device support to use. Naturally, only the devices for which support has been compiled in can be selected.

Here is a table of the possibilities, showing the `MFTERM` value and the corresponding `configure` option(s) in parentheses.

<code>epsf</code>	(‘ <code>--enable-epsfwin</code> ’) Pseudo-window server for Encapsulated PostScript (see <code>web2c/window/epsf.c</code>). This device produces an EPS file containing the graphics which would be displayed online on other devices. The name of the EPS file defaults to <code>metafont.eps</code> but can be changed by setting the <code>MFEPSF</code> environment variable to the new filename. Contributed by Mathias Herberts.
<code>hp2627</code>	(‘ <code>--enable-hp2627win</code> ’) HP2627a color graphics terminals.
<code>mftalk</code>	(‘ <code>--enable-mftalkwin</code> ’) Generic window server (see <code>web2c/window/mftalk.c</code>).■
<code>next</code>	(‘ <code>--enable-next</code> ’) NeXT window system. This requires a separate program, called <code>DrawingServant</code> , available separately. See the <code>web2c/window/next.c</code> .
<code>regis</code>	(‘ <code>--enable-regiswin</code> ’) Regis terminals.
<code>sun</code>	(‘ <code>--enable-suntoolswin</code> ’) The old Suntools (not any flavor of X) window system. (You can get the even older SunWindows <code>gfx</code> system by using <code>sun-gfx.c</code> .)
<code>tek</code>	(‘ <code>--enable-tektronixwin</code> ’) Tektronix terminals.
<code>uniterm</code>	(‘ <code>--enable-unitermwin</code> ’) Uniterm, Simon Poole’s emulator of a smart Tektronix 4014 terminal. This may work with regular Tektronix terminals as well; it’s faster than the driver ‘ <code>--enable-tektronixwin</code> ’ selects.
<code>xterm</code>	‘ <code>--with-x</code> ’ The X window system (version 11). There are two variants of the X11 support, one that works with the Xt toolkit, and another that works directly with Xlib. The Xt support is more efficient and has more functionality, so it is the default. If you must use the Xlib support, use ‘ <code>configure --with-x --with-kf-x-toolkit=no</code> ’. Specify ‘ <code>--disable-mf-nowin</code> ’ in order not to build a separate non-windows-capable Metafont executable <code>mf-nowin</code> (or <code>mf-nowin.exe</code>). You cannot specify any of the usual X options (e.g., ‘ <code>-geometry</code> ’) on the Metafont command line, but you can specify X resources in your <code>~/.Xdefaults</code> or <code>~/.Xresources</code> file. The class name is <code>Metafont</code> . If you’re using the Xt support, all the usual X toolkit resources are supported. If you’re using the Xlib support, only the <code>geometry</code> resource is supported. You specify the X display to which Metafont connects in the <code>DISPLAY</code> environment variable, as usual.

Writing support for a new device is straightforward. Aside from defining the basic drawing routines that Metafont uses (see `mf.web`), you only have to add another entry to

the tables on the last page of `web2c/lib/texmfmp.c`. Or you can write an independent program and use MFtalk (see `web2c/window/mftalk.c`).

6.5 GFtoDVI: Character proofs of fonts

GFtoDVI makes *proof sheets* from a GF bitmap file as output by, for example, Metafont (see Chapter 6 [Metafont], page 26). This is an indispensable aid for font designers or Metafont hackers. Synopsis:

```
gftodvi [option]... gfname[gf]
```

The font *gfname* is searched for in the usual places (see Section “Glyph lookup” in *Kpathsea*). To see all the relevant paths, set the environment variable `KPATHSEA_DEBUG` to ‘-1’ before running the program.

The suffix ‘*gf*’ is supplied if not already present. This suffix is not an extension, no ‘.’ precedes it; for instance, `cmt10.600gf`.

The output filename is the basename of *gfname* extended with `.dvi`, e.g., ‘`gftodvi /wherever/foo.600gf`’ creates `./foo.dvi`.

The characters from *gfname* appear one per page in the DVI output, with labels, titles, and annotations, as specified in Appendix H (Hardcopy Proofs) of *The Metafontbook*.

GFtoDVI uses several fonts besides *gfname* itself:

- *gray font* (default `gray`): for the pixels that actually make up the character. Simply using black is not right, since then labels, key points, and other information could not be shown.
- *title font* (default `cmt8`): for the header information at the top of each output page.
- *label font* (default `cmtt10`): for the labels on key points of the figure.
- *slant font* (no default): for diagonal lines, which are otherwise simulated using horizontal and vertical rules.

To change the default fonts, you must use `special` commands in your Metafont source file, typically via commands like `slantfont slantlj4`. There is no default slant font since no one printer is suitable as a default. You can make your own by copying one of the existing files, such as `.../fonts/source/public/misc/slantlj4.mf` and then running `mf` on it.

For testing purposes, you may it useful to run `mf-nowin rtest` (hit RETURN when it stops) to get a `gf` file of a thorn glyph. Or use `mf` instead of `mf-nowin` to have the glyph(s) displayed on the screen. After that, `gftodvi rtest.2602gf` should produce `rtest.dvi`, which you process as usual.

The program accepts the following option, as well as the standard ‘`-verbose`’, ‘`-help`’, and ‘`-version`’ (see Section 3.2 [Common options], page 6):

`‘-overflow-label-offset=points’`

Typeset the so-called overflow labels, if any, *points* TEX points from the right edge of the character bounding box. The default is a little over two inches (ten million scaled points, to be precise). Overflow equations are used to locate coordinates when their actual position is too crowded with other information.

6.6 MFT: Prettyprinting Metafont source

MFT translates a Metafont program into a \TeX document suitable for typesetting, with the aid of \TeX macros defined in the file `mftmac.tex`. Synopsis:

```
mft [option]... mfname[.mf]
```

MFT searches the usual places for *mfname* (see Section “Supported file formats” in *Kpathsea*). To see all the relevant paths, set the environment variable `KPATHSEA_DEBUG` to ‘`-1`’ before running the program. The output goes to the basename of *mfname* extended with `.tex`, e.g., ‘`mft /wherever/foo.mf`’ creates `./foo.tex`.

Line breaks in the input are carried over into the output; moreover, blank spaces at the beginning of a line are converted to quads of indentation in the output. Thus, you have full control over the indentation and line breaks. Each line of input is translated independently of the others.

Further control is allowed via Metafont comments:

- Metafont comments following a single ‘%’ should be valid \TeX input. But Metafont material can be included within vertical bars in a comment; this will be translated by MFT as if it were regular Metafont code. For example, a comment like ‘% `|x2r|` is the tip of the bowl’ will be translated into the \TeX ‘% `x_{2r}` is the ...’, i.e., the ‘`x2r`’ is treated as an identifier.
- ‘`%%`’ indicates that the remainder of an input line should be copied verbatim to the output. This is typically used to introduce additional \TeX material at the beginning or an MFT job, e.g. code to modify the standard layout or the formatting macros defined in `mftmac.tex`, or to add a line saying ‘`%%\bye`’ at the end of the job. (MFT doesn’t add this automatically in order to allow processing several files produced by MFT in the same \TeX job.)
- ‘`%%% token1 other-tokens`’ introduces a change in MFT’s formatting rules; all the *other-tokens* will henceforth be translated according to the current conventions for *token1*. The tokens must be symbolic (i.e., not numeric or string tokens). For example, the input line

```
%%% addto fill draw filldraw
```

says to format the ‘`fill`’, ‘`draw`’, and ‘`filldraw`’ operations of plain Metafont just like the primitive token ‘`addto`’, i.e., in boldface type. Without such reformatting commands, MFT would treat ‘`fill`’ like an ordinary tag or variable name. In fact, you need a ‘`%%%`’ command even to get parentheses to act like delimiters.

- ‘`%%%%`’ introduces an MFT comment, i.e., MFT ignores the remainder of such a line.
- Five or more ‘%’ signs should not be used.

(The above description was edited from `mft.web`, written by D.E. Knuth.)

The program accepts the following options, as well as the standard ‘`-help`’ and ‘`-version`’ (see Section 3.2 [Common options], page 6):

```
-change=chfile[.ch]
```

Apply the change file *chfile* as with Tangle and Weave (see Chapter 9 [WEB], page 38).

```
'-style=mftfile[.mft]'
```

Read *mftfile* before anything else; a MFT style file typically contains only MFT directives as described above. The default style file is named `plain.mft`, which defines this properly for programs using plain Metafont. The MFT files is searched along the `MFTINPUTS` path; see Section “Supported file formats” in *Kpathsea*.

Other examples of MFT style files are `cmbase.mft`, which defines formatting rules for the macros defined in `cm.base`, and `e.mft`, which was used in the production of Knuth’s Volume E, *Computer Modern Typefaces*.

Using an appropriate MFT style file, it is also possible to configure MFT for typesetting MetaPost sources. However, MFT does not search the usual places for MetaPost input files.

If you use eight-bit characters in the input file, they are passed on verbatim to the `TeX` output file; it is up to you to configure `TeX` to print these properly.

7 MetaPost: Generating PostScript

MetaPost is a picture-drawing language similar to Metafont (see Chapter 6 [Metafont], page 26), but instead of outputting bitmaps in a “font”, it outputs PostScript commands. It’s primarily intended for creating technical illustrations, but can also be used to create PostScript or OpenType fonts (<https://ctan.org/pkg/metatype1>).

MetaPost also provides for arbitrary integration of text and graphics in a natural way, using any typesetter (T_EX and Troff are both supported) and a number of other subsidiary programs, described below.

7.1 `mpost` invocation

MetaPost (installed as `mpost`) reads a series of pictures specified in the MetaPost programming language, and outputs corresponding PostScript code. This section merely describes the options available in the Web2c implementation. For a complete description of the MetaPost language, see AT&T technical report CSTR-162, generally available in `texmf/doc/metapost/`, where `texmf` is the root of T_EX directory structure. The MetaPost home page: <https://tug.org/metapost>.

Also, a standard MetaPost package for drawing graphs is documented in AT&T technical report CSTR-164, available as the file `mpgraph.ps`, generally stored alongside `mpman.ps`.

MetaPost processes its command line and determines its memory dump (mem) file in a way analogous to Metafont and T_EX (see Section 5.1 [tex invocation], page 16, and see Section 4.3 [Memory dumps], page 11). Synopses:

```
mpost [option]... [mpname[.mp]] [mp-commands]
mpost [option]... \first-line
mpost [option]... &mem args
```

MetaPost searches the usual places for the main input file *mpname* (see Section “Supported file formats” in *Kpathsea*), extending *mpname* with `.mp` if necessary. To see all the relevant paths, set the environment variable `KPATHSEA_DEBUG` to ‘-1’ before running the program.

MetaPost writes its PostScript output to a series of files `basempname.nnn` (or perhaps `basempname.ps`, very occasionally `basempname.tfm`), where *nnn* are the figure numbers specified in the input, typically to the `beginfig` macro, and `basempname` is the basename of *mpname*, or ‘`mpout`’ if no input file was specified. MetaPost uses the ‘`.ps`’ extension when the figure number is out of range, e.g., if you say `beginfig(-1)`.

You can use the output files as figures in a T_EX document just as with any other PostScript figures. For example, with this T_EX command:

```
\special{psfile="filename"}
```

or by using `epsf.tex` (see Section “EPSF macros” in *Dvips*).

The MetaPost construct

```
btex ... tex-input ... etex
```

generates a MetaPost picture expression corresponding to *tex-input*.

The construct

```
verbatimtex ... tex-input ... etex
```

simply passes the *tex-input* through to *TeX*. For example, if you are using *L^AT_EX*, your MetaPost input file must start with a `\verbatimtex` block that gives the necessary `\documentclass` (or `\documentstyle`) `\begin{document}` command. You will also need to set the environment variable `TEX` to ‘`latex`’.

tex-input need not be specifically *TeX* input; it could also be *Troff*. In that case, you will need the ‘`-m pictures`’ *Troff* macro package (unfortunately absent from many *Troff* implementations), or an equivalent such as the ‘`-m pspic`’ macros from *GNU groff* described in *grops(1)*.

Naturally, you must use fonts that are supported by the typesetter; specifically, you’ll probably want to use standard PostScript fonts with *Troff*. And only the *TeX* system understands Computer Modern or other Metafont fonts; you can also use PostScript fonts with *TeX*, of course.

MetaPost-generated PostScript figures which do use Computer Modern fonts for labels cannot be directly previewed or printed. Instead, you must include them in a *TeX* document and run the resulting DVI file through *Dvips* to arrange for the downloading of the required fonts (see Section “Fonts in figures” in *Dvips*). To help with this, the MetaPost distribution provides a small *TeX* file `mproof.tex` which is typically called as:

```
tex mproof mp-output-files... ; dvips mproof -o
```

The resulting file `mproof.ps` can then be printed or previewed.

To generate EPSF files, set the internal MetaPost variable `prologues` positive. To make the output files self-contained, use only standard PostScript fonts. MetaPost reads the same `psfonts.map` file as *Dvips*, to determine PostScript fonts that need to be downloaded (see Section “`psfonts.map`” in *Dvips*).

It is possible for *pdfTeX* to read MetaPost output directly; this is in contrast to general EPSF files, which have to be converted for use with PDF output. The easiest way is to name the MetaPost output files with the `.mps` extension. Then the *L^AT_EX* `\includegraphics` command, for example, will be able to read them, even when outputting PDF.

MetaPost can write output files, via the `write` primitive; this opens a security hole. See Section 5.1 [tex invocation], page 16.

The program accepts the following options, as well as the standard ‘`-help`’ and ‘`-version`’ (see Section 3.2 [Common options], page 6):

```
'-[no]-file-line-error'
'-fmt=fmtname'
'-halt-on-error'
'-ini'
'-interaction=string'
'-jobname=string'
'-kpathsea-debug=number'
'-[no]parse-first-line'
'-output-directory'
'-progname=string'
'-recorder'
'-translate-file=texfile'
'-8bit' These options are common to TeX, Metafont, and MetaPost. See Section 3.2 [Common options], page 6.
```

‘-T’
 ‘-troff’ Set the `prologues` internal variable to 1.
 ‘-tex=*texprogram*’
 When this option is given, the program *texprogram* is used to typeset the labels.

7.2 Initial MetaPost

As of MetaPost 1.504 (TeX Live 2011), MetaPost no longer dumps `.mem` files (see Section 4.3 [Memory dumps], page 11) and does not distinguish virgin and initial forms (see Section 4.2 [Initial and virgin], page 11). Instead, the “initial” file name is read in its source form—that is, `mpost.mp` when the program is invoked as `mpost`.

For a list of options and other information, see Section 7.1 [mpost invocation], page 33.

MetaPost provides a format with all the features of plain Metafont, called `mfplain`. You can use that in the same way; just run `mfplain` instead of `mpost`. This lets you directly process Metafont source files with MetaPost, producing character proofs (one file for each character) similar to those produced with Metafont in proof mode and GFtoDVI (see Section 6.5 [gftodvi invocation], page 30).

7.3 DVIToMP: DVI to MPX conversion

DVIToMP converts DVI files into low-level MetaPost commands in a so-called MPX file. Synopsis:

`dvitomp dvifile[.dvi] [mpxfile[.mpx]]`

If *mpxfile* is not specified, the output goes to the basename of *dvifile* extended with `.mpx`, e.g., ‘`dvitomp /wherever/foo.dvi`’ creates `./foo.mpx`.

DVIToMP supports Dvips-style color specials, such as ‘`color push name`’ and ‘`color pop`’, outputting them as `withcolor` MetaPost commands.

The only options are ‘`-help`’ and ‘`-version`’ (see Section 3.2 [Common options], page 6).

8 Bib_T_EX: Bibliographies

Bib_T_EX automates much of the job of typesetting bibliographies, and makes bibliography entries reusable in many different contexts.

8.1 Bib_T_EX invocation

Bib_T_EX creates a printable bibliography (`.bb1`) file from references in a `.aux` file, generally written by _T_EX or _L_A_T_EX. The `.bb1` file is then incorporated on a subsequent run. The basic bibliographic information comes from `.bib` files, and a Bib_T_EX style (`.bst`) file controls the precise contents of the `.bb1` file. Synopsis:

```
bibtex [option]... auxfile[.aux]
```

The output goes to the basename of `auxfile` extended with `.bb1`; for example, ‘`bibtex /wherever/foo.aux`’ creates `./foo.bb1`. Bib_T_EX also writes a log file to the basename of `auxfile` extended with ‘`.blg`’.

The names of the `.bib` and `.bst` files are specified in the `.aux` file as well, via the `\bibliography` and `\bibliographystyle` (La)T_EX macros. Bib_T_EX searches for `.bib` files using the `BIBINPUTS` and `TEXBIB` paths, and for `.bst` files using `BSTINPUTS` (see Section “Supported file formats” in *Kpathsea*). It does no path searching for `.aux` files.

The program accepts the following options, as well as the standard ‘`-help`’ and ‘`-version`’ (see Section 3.2 [Common options], page 6):

‘`-terse`’ Suppress the program banner and progress reports normally output.

‘`-min-crossrefs=n`’

If at least *n* (2 by default) bibliography entries refer to another entry *e* via their `crossref` field, include *e* in the `.bb1` file, even if it was not explicitly referenced in the `.aux` file. For example, *e* might be a conference proceedings as a whole, with the cross-referencing entries being individual articles published in the proceedings.

If you want to avoid these automatic inclusions altogether, make *n* a sufficiently large number, and be sure to remove any previous `.aux` and `.bb1` files. Otherwise the option may appear to have no effect, since Bib_T_EX will have added the citation for *e* to the `.aux`, and nothing will remove it.

See also:

`btxdoc.tex`

Basic L_A_T_EXable documentation for general Bib_T_EX users.

`btxhak.tex`

L_A_T_EXable documentation for style designers.

`btxdoc.bib`

Bib_T_EX database file for the two above documents.

`xampl.bib`

Example database file with all the standard entry types.

`ftp://ftp.math.utah.edu/pub/tex/bib/`

A very large `.bib` and `.bst` collection, including references for all the standard T_EX books and a complete bibliography for TUGboat.

8.2 Basic Bib \TeX style files

Here are descriptions of the four standard and four semi-standard basic Bib \TeX styles. *CTAN:/biblio/bibtex* contains these and many more (for CTAN info, see Section “unix-tex.ftp” in *Kpathsea*).

- plain** Sorts entries alphabetically, with numeric labels. Generally formatted according to van Leunen’s *A Handbook for Scholars*. The other style files listed here are based on **plain**.
- abbrv** First names, month names, and journal names are abbreviated.
- acm** Names are printed in small caps.
- alpha** Alphanumeric labels, e.g., ‘Knu66’.
- apalike** No labels at all; instead, the year appears in parentheses after the author. Use this in conjunction with **apalike.tex** (plain \TeX) or **apalike.sty** (\LaTeX), which also changes the citations in the text to be ‘(**author, year**)’.
- ieeetr** Numeric labels, entries in citation order, IEEE abbreviations, article titles in quotes.
- siam** Numeric labels, alphabetic order, *Math. Reviews* abbreviations, names in small caps.
- unsrt** Lists entries in citation order, i.e., unsorted.

btxbst.doc

The template file and documentation for the standard styles.

9 WEB: Literate programming

WEB languages allow you to write a single source file that can produce both a compilable program and a well-formatted document describing the program in as much detail as you wish to prepare. Writing in this kind of dual-purpose language is called *literate programming*. (The Usenet newsgroup `comp.programming.literate` is devoted to this subject.)

WEB-like languages have been implemented with many pairs of base languages: Cweb provides C and Troff (see Appendix B [References], page 55); CWEB provides C and TEX (CTAN:/web/c_cpp/cweb); Spiderweb provides C, C++, Awk, Ada, many others, and TEX (CTAN:/web/spiderweb); and, of course, the original WEB provides Pascal and TEX, the implementation languages for the original TEX, Metafont, MetaPost, and related programs to come from the TEX project at Stanford.

The original WEB language is documented in the file `webman.tex`, which is included in the `ftp://ftp.tug.org/tex/lib.tar.gz` archive (and available in many other places, of course).

9.1 Tangle: Translate WEB to Pascal

Tangle creates a compilable Pascal program from a WEB source file (see Chapter 9 [WEB], page 38). Synopsis:

```
tangle [option]... webfile[.web] [changefile[.ch]]
```

The Pascal output is written to the basename of *webfile* extended with ‘.p’; for example, ‘`tangle /wherever/foo.web`’ creates `./foo.p`. Tangle applies *changefile* to *webfile* before writing the output; by default, there is no change file.

If the program makes use of the WEB string facility, Tangle writes the string pool to the basename of *webfile* extended with ‘.pool’.

The Pascal output is packed into lines of 72 characters or less, with the only concession to readability being the termination of lines at semicolons when this can be done conveniently.

The program accepts the following options, as well as the standard ‘`--help`’ and ‘`--version`’ (see Section 3.2 [Common options], page 6):

`'-length=number'`

The number of characters that are considered significant in an identifier. Whether underline characters are counted depends on the ‘`-underline`’ option. The default value is 32, the original tangle used 7, but this proved too restrictive for use by Web2c.

`'-lowercase'`

`'-mixedcase'`

`'-uppercase'`

These options specify the case of identifiers in the output of tangle. If ‘`-uppercase`’ (‘`-lowercase`’) is specified, tangle will convert all identifiers to uppercase (lowercase). The default is ‘`-mixedcase`’, which specifies that the case will not be changed.

`'-underline'`

When this option is given, tangle does not strip underline characters from identifiers.

`'-loose'`

`'-strict'` These options specify how strict tangle must be when checking identifiers for equality. The default is `'-loose'`, which means that tangle will follow the rules set by the case-smashing and underline options above. If `'-strict'` is set, then identifiers will always be stripped of underlines and converted to uppercase before checking whether they collide.

9.2 Weave: Translate WEB to T_EX

Weave creates a T_EX document from a WEB source file (see Chapter 9 [WEB], page 38), assuming various macros defined in `webmac.tex`. It takes care of typographic details such as page layout, indentation, and italicizing identifiers. It also automatically gathers and outputs extensive cross-reference information. Synopsis:

```
weave [option]... webfile[.web] [changefile[.ch]]
```

The output is to the basename of `webfile` extended with `'.tex'`; for example, `'weave /wherever/foo.web'` creates `./foo.tex`. Weave applies `changefile` to `webfile` before writing the output; by default, there is no change file.

The program accepts the following option, as well as the standard `'-verbose'`, `'-help'` and `'-version'` (see Section 3.2 [Common options], page 6):

`'-x'`

Omit the cross-reference information: the index, the list of WEB module names, and the table of contents (an empty `CONTENTS.tex` file will still be written when the Weave output file is processed by T_EX using the default `webmac.tex`, though).

Conventionally, WEB programmers should define the T_EX `\title` macro at the beginning of the source file. Also, to get output of only changed modules, one can say `\let\maybe=\iffalse` (usually as the first change in the change file).

9.3 Pooltype: Display WEB pool files

Pooltype shows the so-called *string number* of each string in a WEB pool file (see Chapter 9 [WEB], page 38), as output by Tangle (see Section 9.1 [tangle invocation], page 38), including the first 256 strings corresponding to the possible input characters. Pooltype primarily serves as an example of WEB conventions to implementors of the T_EX system. Synopsis:

```
pooltype [option]... poolfile[.pool]
```

No path searching is done for `poolfile`. Output is to standard output.

The only options are `--help` and `--version` (see Section 3.2 [Common options], page 6).

As an example of the output, here is the (edited) output for `tex.pool`:

```
0: "^^@"
1: "^^A"
...
255: "^^ff"
256: "pool size"
...
1314: "Using character substitution: "
```

(23617 characters in all.)

In Metafont and MetaPost, the first 256 characters are actually represented as single bytes (i.e., themselves), not in the ‘`^^`’ notation. Consider Pooltype as showing the results after conversion for output.

10 DVI utilities

\TeX outputs a file in *DVI* (DeVice Independent) format as a compact representation of the original document. DVI files can be translated to meet the requirements of a real physical device, such as PostScript printers (see Section “Introduction” in *Dvips*), PCL printers (see *dvilj(1)*), and X displays (see *xdvi(1)*). In fact, DVI translators are available for virtually all common devices: see *CTAN:/dviware* (for CTAN info, see Section “*unixtex.ftp*” in *Kpathsea*).

For the precise definition of the DVI file format, see (for example) the source file *web2c/dvitype.web*.

The DVI-processing programs in the Web2c distribution are not device drivers; they perform generic utility functions.

10.1 DVICopy: Canonicalize virtual font references

DVICopy reads a DVI file, expands any references to virtual fonts (see Section “Virtual fonts” in *Dvips*) to base fonts, and writes the resulting DVI file. Thus you can use virtual fonts even if your DVI processor does not support them, by passing the documents through DVICopy first. Synopsis:

```
dvicopy [option]... [indvi[.dvi] [outdvi[.dvi]]]
```

DVICopy reads standard input if *indvi* is not specified, and writes standard output if *outdvi* is not specified.

The program accepts the following options, as well as the standard ‘-help’ and ‘-version’ (see Section 3.2 [Common options], page 6):

‘-magnification=*integer*’

Override existing magnification in *indvi* with *integer*; 1000 specifies no magnification. This is equivalent to setting \TeX ’s $\backslash\text{mag}$ parameter.

‘-max-pages=*n*’

Process *n* pages; default is one million.

‘-page-start=page-spec’

Start at the first page matching *page-spec*, which is one or more (signed) integers separated by periods, corresponding to \TeX ’s $\backslash\text{count0}\dots\text{9}$ parameters at $\backslash\text{shipout}$ time; ‘*’ matches anything. Examples: ‘3’, ‘1.*.-4’.

10.2 DVIType: Plain text transliteration of DVI files

DVIType translates a DeVice Independent (DVI) file (as output by \TeX , for example) to a plain text file that humans can read. It also serves as a DVI-validating program, i.e., if DVIType can read a file, it’s correct. Synopsis:

```
dvitype [option]... dvifile[.dvi]
```

DVIType does not read any bitmap files, but it does read TFM files for fonts referenced in *dvifile*. The usual places are searched (see Section “Supported file formats” in *Kpathsea*). To see all the relevant paths, set the environment variable *KPATHSEA_DEBUG* to ‘-1’ before running the program.

Output goes to standard output.

The program accepts the following options, as well as the standard ‘-help’ and ‘-version’ (see Section 3.2 [Common options], page 6):

‘-dpi=*real*’

Do pixel movement calculations at *real* pixels per inch; default 300.0.

‘-magnification=*integer*’

Override existing magnification in *indvi* with *integer*; 1000 specifies no magnification. This is equivalent to setting TeX’s \mag parameter.

‘-max-pages=*n*’

Process *n* pages; default is one million.

‘-output-level=*n*’

Verbosity level of output, from 0 to 4 (default 4):

- 0: Global document information only.
- 1: Most DVI commands included, and typeset characters summarized.
- 2: Character and movement commands explicitly included.
- 3: DVI stack and current position calculations included.
- 4: Same information as level 3, but DVItypes does random positioning in the file, reading the DVI postamble first.

‘-page-start=*page-spec*’

Start at the first page matching *page-spec*, which is one or more (signed) integers separated by periods, corresponding to TeX’s \count0...9 parameters at \shipout time; ‘*’ matches anything. Examples: ‘1’, ‘5.*.-9’.

‘-show-opcodes’

Show numeric opcode values (in decimal) for DVI commands, in braces after the command name. This can help in debugging DVI utilities. We use decimal because in the DVI format documentation (in dvitype.web, among others) the opcodes are shown in decimal.

10.2.1 DVItypes output example

As an example of the output from DVItypes (see section above), here is its (abridged) translation of the story.dvi resulting from running the example in *The TeXbook*, with ‘-output-level=4’ and ‘-show-opcodes’ on.

```
...
Options selected:
Starting page = *
Maximum number of pages = 1000000
Output level = 4 (the works)
Resolution = 300.0000000 pixels per inch
numerator/denominator=25400000/473628672
magnification=1000;      0.00006334 pixels per DVI unit
' TeX output 1992.05.17:0844'
Postamble starts at byte 564.
```

```

maxv=43725786, maxh=30785863, maxstackdepth=3, totalpages=1
Font 33: cmsl10---loaded at size 655360 DVI units
Font 23: cmbx10---loaded at size 655360 DVI units
Font 0: cmr10---loaded at size 655360 DVI units

42: beginning of page 1
87: push {141}
level 0:(h=0,v=0,w=0,x=0,y=0,z=0,hh=0,vv=0)
88: down3 -917504 {159} v:=0-917504=-917504, vv:=-58
92: pop {142}
...
104: putrule {137} height 26214, width 30785863 (2x1950 pixels)
113: down3 5185936 {159} v:=655360+5185936=5841296, vv:=370
117: push {141}
level 1:(h=0,v=5841296,w=0,x=0,y=0,z=0,hh=0,vv=370)
118: right4 12265425 {146} h:=0+12265425=12265425, hh:=777
[ ]
123: fntdef1 23 {243}: cmbx10
145: fntnum23 {194} current font is cmbx10
146: setchar65 h:=12265425+569796=12835221, hh:=813
147: w3 251220 {150} h:=12835221+251220=13086441, hh:=829
151: setchar83 h:=13086441+418700=13505141, hh:=856
...
164: setchar82 h:=17448202+565245=18013447, hh:=1142
165: x0 -62805 {152} h:=18013447-62805=17950642, hh:=1138
166: setchar89 h:=17950642+569796=18520438, hh:=1174
[A SHORT STORY]
167: pop {142}
level 1:(h=0,v=5841296,w=0,x=0,y=0,z=0,hh=0,vv=370)
...
550: pop {142}
level 0:(h=0,v=42152922,w=0,x=0,y=0,z=0,hh=0,vv=2670)
551: down3 1572864 {159} v:=42152922+1572864=43725786, vv:=2770
555: push {141}
level 0:(h=0,v=43725786,w=0,x=0,y=0,z=0,hh=0,vv=2770)
556: right4 15229091 {146} h:=0+15229091=15229091, hh:=965
561: setchar49 h:=15229091+327681=15556772, hh:=986
[ 1]
562: pop {142}
level 0:(h=0,v=43725786,w=0,x=0,y=0,z=0,hh=0,vv=2770)
563: eop {140}

```

Explanation:

- The DVItype options are recorded at the beginning, followed by global information about the document, including fonts used.
- Each DVI command is preceded by its byte position in the file ('42:', '87:', ...),

and (because of the ‘`-show-opcodes`’) followed by its decimal opcode value in braces (‘`{141}`’, ‘`{142}`’, …).

- The ‘`level`’ lines record information about the DVI stack; ‘`h`’ and ‘`v`’ define the current position in DVI units, while ‘`hh`’ and ‘`vv`’ are the same in pixels.
- Text sequences are summarized in brackets, as in ‘`[A SHORT STORY]`’ and the ‘`[1]`’.

11 Font utilities

The Web2c programs described here convert between various T\textrm{E}\textrm{X}-related font formats; the first section below briefly describes the formats. GFtoPK is the only one that is routinely used, as Metafont outputs GF format, but it's most efficient for device drivers to use PK.

The precise definitions of the PK, GF, TFM, PL, VF, and VPL formats mentioned below are in the source files that read them; `pktype.web`, `gftype.web`, `tftopl.web`, etc.

11.1 Font file formats

(For another perspective on this, see Section “Font concepts” in *Dvips*).

Font files come in several varieties, with suffixes like:

`.tfm` `.*pk` `.*gf` `.*pxl` (obsolete) `.pl` `.mf` `.vf` `.vpl`

Each represents a file format.

A TFM (T\textrm{E}\textrm{X} font metric) file is a compact binary file that contains information about each character in a font, about combinations of characters within that font, and about the font as a whole. The font metric information contained in TFM files is device-independent units is used by T\textrm{E}\textrm{X} to do typesetting. Unlike the bitmap (raster) fonts described below, TFM font files contain no information about the shapes of characters. They describe rectangular areas and combinations thereof, but not what will eventually be printed in those areas.

Since T\textrm{E}\textrm{X} does scaling calculations, one TFM file serves for all magnifications of a given typeface. On the other hand, the best printed results are obtained when magnified (or reduced fonts) are not produced geometrically (as done by PostScript, for example) but rather optically, with each size a separate design (as done with Computer Modern and the EC fonts, for example); then a separate TFM file is needed for each size.

At any rate, T\textrm{E}\textrm{X} produces a DVI (DeVice Independent) file from your source document. In order to print DVI files on real devices, you need font files defining digitized character shapes and other data. Then previewers and printer-driver programs can translate your DVI files into something usable by your monitor or printer. Bitmap fonts come with suffixes such as ‘`.600pk`’ or ‘`.600gf`’ or ‘`.3000pxl`’, where the ‘600’ is the horizontal dots-per-inch resolution at which the font was produced, and the ‘pk’ or ‘gf’ or ‘pxl’ indicates the font format. Outline fonts in PostScript Type 1 format have suffixes such as ‘`.pfa`’ or ‘`.pfb`’.

Fonts in pk (packed) format are in the tightly packed raster format that is pretty much the standard today. They take up less space than fonts in the gf (generic font) format that Metafont generates, and far less space than fonts in pxl format. Fonts in pxl format take up gross amounts of disk space and permit only 128 characters. They are obsolete.

Font files with the ‘`.pl`’ (property list) suffix are the plain text (human-readable) analog of the binary ‘`.tfm`’ files. The `TFtoPL` and `PLtoTF` programs convert between the two formats (see Section 11.6 [`tftopl` invocation], page 50, and Section 11.7 [`pltotf` invocation], page 52).

Font files with the ‘`.mf`’ suffix are in Metafont source format. These are the files used by Metafont to generate rastered fonts for specific typefaces at specific magnifications for the specific resolution and type of mapping used by your device.

The suffix ‘.vf’ identifies “virtual font” files, for which ‘.vp1’ is the human-readable analog. See See Section 11.8 [vftovp invocation], page 52, and Section 11.9 [vptovf invocation], page 53. For further discussion of virtual fonts, see *CTAN:/doc/virtual-fonts.knuth*, *CTAN:/help/virtualfonts.txt*, and Section “Virtual fonts” in *Dvips*.

(This section is based on documentation in the original Unix TeX distribution by Pierre MacKay and Elizabeth Tachikawa.)

11.2 GFtoPK: Generic to packed font conversion

GFtoPK converts a generic font (GF) file output by, for example, Metafont (see Section 6.1 [mf invocation], page 26) to a packed font (PK) file. PK files are considerably smaller than the corresponding gf files, so they are generally the bitmap font format of choice. Some DVI-processing programs, notably Dvips, only support PK files and not GF files. Synopsis:

```
gftopk [option]... gfname.dpi[gf] [pkfile]
```

The font *gfname* is searched for in the usual places (see Section “Glyph lookup” in *Kpathsea*). To see all the relevant paths, set the environment variable **KPATHSEA_DEBUG** to ‘-1’ before running the program.

The suffix ‘*gf*’ is supplied if not already present. This suffix is not an extension; no ‘.’ precedes it: for instance, *cmar10.600gf*.

If *pkfile* is not specified, the output is written to the basename of ‘*gfname.dpi*’, e.g., ‘*gftopk /wherever/cmar10.600gf*’ creates *./cmar10.600pk*.

The only options are ‘--verbose’, ‘--help’, and ‘--version’ (see Section 3.2 [Common options], page 6).

11.3 PKtoGF: Packed to generic font conversion

PKtoGF converts a packed font (PK) file to a generic font (GF) file. Since PK format is much more compact than GF format, the most likely reason to do this is to run GFType (see Section 11.5 [gftype invocation], page 48) on the result, so you can see the bitmap images. Also, a few old utility programs do not support PK format. Synopsis:

```
pktogf [option]... pkname.dpi[pk] [gffile]
```

The font *pkname* is searched for in the usual places (see Section “Glyph lookup” in *Kpathsea*). To see all the relevant paths, set the environment variable **KPATHSEA_DEBUG** to ‘-1’ before running the program.

The suffix ‘*pk*’ is supplied if not already present. This suffix is not an extension; no ‘.’ precedes it: for instance, *cmar10.600pk*.

If *gffile* is not specified, the output is written to the basename of ‘*pkname.dpi*’, e.g., ‘*pktogf /wherever/cmar10.600pk*’ creates *./cmar10.600gf*.

The only options are ‘--verbose’, ‘--help’, and ‘--version’ (see Section 3.2 [Common options], page 6).

11.4 PKtype: Plain text transliteration of packed fonts

PKtype translates a packed font (PK) bitmap file (as output by GFtoPK, for example) to a plain text file that humans can read. It also serves as a PK-validating program, i.e., if PKtype can read a file, it’s correct. Synopsis:

```
pktype pkname.dpi[pk]
```

The font *pkname* is searched for in the usual places (see Section “Glyph lookup” in *Kpathsea*). To see all the relevant paths, set the environment variable `KPATHSEA_DEBUG` to ‘-1’ before running the program.

The suffix ‘pk’ is supplied if not already present. This suffix is not an extension; no ‘.’ precedes it: for instance, `cmr10.600pk`.

The translation is written to standard output.

The only options are ‘`-help`’ and ‘`-version`’ (see Section 3.2 [Common options], page 6).

As an example of the output, here is the (abridged) translation of the letter ‘K’ in ‘`cmr10`’, as rendered at 600 dpi with the mode ‘`ljfour`’ from `modes.mf` (available from <ftp://ftp.tug.org/tex/modes.mf>).

```
955: Flag byte = 184 Character = 75 Packet length = 174
      Dynamic packing variable = 11
      TFM width = 815562 dx = 4259840
      Height = 57 Width = 57 X-offset = -3 Y-offset = 56
      [2]23(16)17(8)9(25)11(13)7(27)7(16)7(28)4(18)7(28)2(20)7(27)...
      ...
      (14)9(24)12(5) [2]23(13)21
```

Explanation:

‘955’ The byte position in the file where this character starts.

‘Flag byte’

‘Dynamic packing variable’

Related to the packing for this character; see the source code.

‘Character’

The character code, in decimal.

‘Packet length’

The total length of this character definition, in bytes.

‘TFM width’

The device-independent (TFM) width of this character. It is 2^{24} times the ratio of the true width to the font’s design size.

‘dx’

The device-dependent width, in *scaled pixels*, i.e., units of horizontal pixels times 2^{16} .

‘Height’

‘Width’ The bitmap height and width, in pixels.

‘X-offset’

‘Y-offset’

Horizontal and vertical offset from the upper left pixel to the reference (origin) pixel for this character, in pixels (right and down are positive). The *reference pixel* is the pixel that occupies the unit square in Metafont; the Metafont reference point is the lower left hand corner of this pixel. Put another way, the x-offset is the negative of the left side bearing; the right side bearing is the horizontal escapement minus the bitmap width plus the x-offset.

'[2]23(16)…'

Finally, run lengths of black pixels alternate with parenthesized run lengths of white pixels, and brackets indicate a repeated row.

11.5 GFtype: Plain text transliteration of generic fonts

GFtype translates a generic font (GF) bitmap file (as output by Metafont, for example) to a plain text file that humans can read. It also serves as a GF-validating program, i.e., if GFtype can read a file, it's correct. Synopsis:

```
gftype [option]... gfname.dpi[gf]
```

The font *gfname* is searched for in the usual places (see Section “Glyph lookup” in *Kpathsea*). To see all the relevant paths, set the environment variable `KPATHSEA_DEBUG` to ‘-1’ before running the program.

The suffix ‘*gf*’ is supplied if not already present. This suffix is not an extension; no ‘.’ precedes it: for instance, `cmr10.600gf`.

The translation is written to standard output.

The program accepts the following options, as well as the standard ‘`-help`’ and ‘`-version`’ (see Section 3.2 [Common options], page 6):

‘`-images`’ Show the characters’ bitmaps using asterisks and spaces.

‘`-mnemonics`’

Translate all commands in the GF file.

As an example of the output, here is the (abridged) translation of the letter ‘K’ in ‘`cmr10`’, as rendered at 600 dpi with the mode ‘`ljfour`’ from `modes.mf` (available from <ftp://ftp.tug.org/tex/modes.mf>), with both ‘`-mnemonics`’ and ‘`-images`’ enabled.

GFtype outputs the information about a character in two places: a main definition and a one-line summary at the end. We show both. Here is the main definition:

```
2033: beginning of char 75: 3<=m<=60 0<=n<=56
  (initially n=56) paint (0)24(12)20
  2043: newrow 0 (n=55) paint 24(12)20
  2047: newrow 0 (n=54) paint 24(12)20
  2051: newrow 0 (n=53) paint 24(12)20
  2055: newrow 7 (n=52) paint 10(21)13
  2059: newrow 8 (n=51) paint 8(23)9
  ...
  2249: newrow 8 (n=5) paint 8(23)11
  2253: newrow 7 (n=4) paint 10(22)12
  2257: newrow 0 (n=3) paint 24(11)22
  2261: newrow 0 (n=2) paint 24(11)22
  2265: newrow 0 (n=1) paint 24(11)22
  2269: newrow 0 (n=0) paint 24(11)22
  2273: eoc
```

```
.<--This pixel's lower left corner is at (3,57) in METAFONT coordinates
*****
*****
*****
*****
*****
*****
*****
...
*****
*****
*****
*****
*****
*****
*****
*****
.>--This pixel's upper left corner is at (3,0) in METAFONT coordinates
```

Explanation:

‘2033’

‘2043’

‘...’ The byte position in the file where each GF command starts.

‘beginning of char 75’

The character code, in decimal.

‘ $3 \leq m \leq 60$ $0 \leq n \leq 56$ ’

The character’s bitmap lies between 3 and 60 (inclusive) horizontally, and between 0 and 56 (inclusive) vertically. (m is a column position and n is a row position.) Thus, 3 is the left side bearing. The right side bearing is the horizontal escapement (given below) minus the maximum m .

‘(initially $n=56$) paint (0)24(12)20’

The first row of pixels: 0 white pixels, 24 black pixels, 12 white pixels, etc.

‘newrow 0 ($n=55$) paint 24(12)20’

The second row of pixels, with zero leading white pixels on the row.

‘eoc’ The end of the main character definition.

Here is the GF postamble information that GFtype outputs at the end:

Character 75: dx 4259840 (65), width 815562 (64.57289), loc 2033

Explanation:

‘dx’ The device-dependent width, in *scaled pixels*, i.e., units of horizontal pixels times 2^{16} . The ‘(65)’ is simply the same number rounded. If the vertical escapement is nonzero, it would appear here as a ‘dy’ value.

‘width’ The device-independent (TFM) width of this character. It is 2^{24} times the ratio of the true width to the font’s design size. The ‘64.57289’ is the same number converted to pixels.

‘loc’ The byte position in the file where this character starts.

11.6 TFtoPL: TeX font metric to property list conversion

TFtoPL translates a TeX font metric (TFM, see Section “Metric files” in *Dvips*) file (as output by Metafont, for example) to *property list format* (a list of parenthesized items describing the font) that humans can edit or read. This program is mostly used by people debugging TeX implementations, writing font utilities, etc. Synopsis:

```
tftopl [option]... tfmname[.tfm] [plfile[.pl]]
```

The font *tfmname* (extended with ‘.tfm’ if necessary) is searched for in the usual places (see Section “Supported file formats” in *Kpathsea*). To see all the relevant paths, set the environment variable *KPATHSEA_DEBUG* to ‘-1’ before running the program.

If *plfile* (which is extended with ‘.pl’ if necessary) is not specified, the property list file is written to standard output. The property list file can be converted back to TFM format by the companion program TFtoPL (see the next section).

The program accepts the following option, as well as the standard ‘-verbose’, ‘-help’ and ‘-version’ (see Section 3.2 [Common options], page 6):

‘-charcode-format=*type*’

Output character codes in the PL file according to *type*: either ‘octal’ or ‘ascii’. Default is ‘ascii’ for letters and digits, octal for all other characters. Exception: if the font’s coding scheme starts with ‘TeX math sy’ or ‘TeX math ex’, all character codes are output in octal.

In ‘ascii’ format, character codes that correspond to graphic characters, except for left and right parentheses, are output as a ‘C’ followed by the single character: ‘C K’, for example. In octal format, character codes are output as the letter ‘O’ followed by octal digits, as in ‘O 113’ for ‘K’.

‘octal’ format is useful for symbol and other non-alphabetic fonts, where using ASCII characters for the character codes is merely confusing.

As an example of the output, here is the (abridged) property list translation of *cmr10.tfm*:

```
(FAMILY CMR)
(FACE 0 352)
(CODINGSCHEME TEX TEXT)
(DESIGNSIZE R 10.0)
(COMMENT DESIGNSIZE IS IN POINTS)
(COMMENT OTHER SIZES ARE MULTIPLES OF DESIGNSIZE)
(CHECKSUM O 11374260171)
(FONTDIMEN
  (SLANT R 0.0)
  (SPACE R 0.333334)
  (STRETCH R 0.166667)
  (SHRINK R 0.111112)
  (XHEIGHT R 0.430555)
  (QUAD R 1.000003)
  (EXTRASPACE R 0.111112)
  )
(LIGTABLE
```

```

...
(LABEL C f)
(LIG C i 0 14)
(LIG C f 0 13)
(LIG C l 0 15)
(KRN 0 47 R 0.077779)
(KRN 0 77 R 0.077779)
(KRN 0 41 R 0.077779)
(KRN 0 51 R 0.077779)
(KRN 0 135 R 0.077779)
(STOP)
...
)
...
(CHARACTER C f
  (CHARWD R 0.305557)
  (CHARHT R 0.694445)
  (CHARIC R 0.077779)
  (COMMENT
    (LIG C i 0 14)
    (LIG C f 0 13)
    (LIG C l 0 15)
    (KRN 0 47 R 0.077779)
    (KRN 0 77 R 0.077779)
    ...
  )
)
...

```

As you can see, the general format is a list of parenthesized *properties*, nested where necessary.

- The first few items (**FAMILY**, **FACE**, and so on) are the so-called *headerbyte* information from Metafont, giving general information about the font.
- The **FONTDIMEN** property defines the **TEX \fontdimen** values.
- The **LIGTABLE** property defines the ligature and kerning table. **LIG** properties define ligatures: in the example above, an ‘f’ (in the ‘LABEL’) followed by an ‘i’ is a ligature, i.e., a typesetting program like **TEX** replaces those two consecutive characters by the character at position octal ’014 in the current font—presumably the ‘fi’ ligature. **KRN** properties define kerns: if an ‘f’ is followed by character octal ’047 (an apostrophe), **TEX** inserts a small amount of space between them: 0.077779 times the design size the font was loaded at (about three-quarters of a printer’s point by default in this case, or .001 inches).
- The **CHARACTER** property defines the dimensions of a character: its width, height, depth, and italic correction, also in design-size units, as explained in the previous item. For our example ‘f’, the depth is zero, so that property is omitted. **TFtoPL** also inserts any kerns and ligatures for this character as a comment.

11.7 PLtoTF: Property list to TeX font metric conversion

PLtoTF translates a property list file (as output by TFtoPL, for example) to TeX font metric (TFM, see Section “Metric files” in *Dvips*) format. It’s much easier for both programs and humans to create the (plain text) property list files and let PLtoTF take care of creating the binary TFM equivalent than to output TFM files directly. Synopsis:

```
pltotf [option]... plfile[.pl] [tfmfile[.tfm]]
```

If *tfmfile* (extended with ‘.tfm’ if necessary) is not specified, the TFM file is written to the basename of ‘*plfile.tfm*’, e.g., ‘*pltotf /wherever/cmr10.pl*’ creates *./cmr10.tfm*. (Since TFM files are binary, writing to standard output by default is undesirable.)

The only options are ‘**-verbose**’, ‘**-help**’, and ‘**-version**’ (see Section 3.2 [Common options], page 6).

For an example of property list format, see the previous section.

11.8 VFtoVP: Virtual font to virtual property lists

VFtoVP translates a virtual font metric (VF, see Section “Virtual fonts” in *Dvips*) file and its accompanying TeX font metric (TFM, see Section “Metric files” in *Dvips*) file (as output by VPtoVF, for example) to *virtual property list format* (a list of parenthesized items describing the virtual font) that humans can edit or read. This program is mostly used by people debugging virtual font utilities. Synopsis:

```
vftovp [option]... vfname[.vf] [tfmname[.tfm] [vplfile[.vpl]]]
```

The fonts *vfname* and *tfmname* (extended with ‘.vf’ and ‘.tfm’ if necessary) are searched for in the usual places (see Section “Supported file formats” in *Kpathsea*). To see all the relevant paths, set the environment variable **KPATHSEA_DEBUG** to ‘-1’ before running the program. If *tfmname* is not specified, *vfname* (without a trailing ‘.vf’) is used.

If *vplfile* (extended with ‘.vpl’ if necessary) is not specified, the property list file is written to standard output. The property list file can be converted back to VF and TFM format by the companion program VFtoVP (see the next section).

The program accepts the following option, as well as the standard ‘**-verbose**’, ‘**-help**’ and ‘**-version**’ (see Section 3.2 [Common options], page 6):

‘-charcode-format=type’

Output character codes in the PL file according to *type*: either ‘**octal**’ or ‘**ascii**’. Default is ‘**ascii**’ for letters and digits, octal for all other characters. Exception: if the font’s coding scheme starts with ‘**TeX math sy**’ or ‘**TeX math ex**’, all character codes are output in octal.

In ‘**ascii**’ format, character codes that correspond to graphic characters, except for left and right parentheses, are output as a ‘C’ followed by the single character: ‘C K’, for example. In octal format, character codes are output as the letter ‘O’ followed by octal digits, as in ‘O 113’ for ‘K’.

‘**octal**’ format is useful for symbol and other non-alphabetic fonts, where using ASCII characters for the character codes is merely confusing.

11.9 VPtoVF: Virtual property lists to virtual font

VPtoVF translates a virtual property list file (as output by VFtoVP, for example) to virtual font (VF, see Section “Virtual fonts” in *Dvips*) and TeX font metric (TFM, see Section “Metric files” in *Dvips*) files. It’s much easier for both programs and humans to create the (plain text) property list files and let VPtoVF take care of creating the binary VF and TFM equivalents than to output them directly. Synopsis:

```
vptovf [option]... vplfile[.vpl] [vffile[.vf] [tfmfile[.tfm]]]
```

If *vffile* (extended with ‘.vf’ if necessary) is not specified, the VF output is written to the basename of ‘*vplfile.vf*'; similarly for *tfmfile*. For example, ‘*vptovf /wherever/ptmr.vpl*’ creates *./ptmr.vf* and *./ptmr.tfm*.

The only options are ‘*-verbose*’, ‘*-help*’, and ‘*-version*’ (see Section 3.2 [Common options], page 6).

11.10 Font utilities available elsewhere

The Web2c complement of font utilities merely implements a few basic conversions. Many other more sophisticated font utilities exist; most are in *CTAN:/fonts/utilities* (for CTAN info, see Section “unixtex.ftp” in *Kpathsea*). Here are some of the most commonly-requested items:

- AFM (Adobe font metric) to TFM conversion: see Section “Invoking afm2tfm” in *Dvips*, and *CTAN:/fonts/utilities/afmtop1*.
- BDF (the X bitmap format) conversion: <ftp://ftp.tug.org/tex/bdf.tar.gz>.
- Creating fonts using MetaPost: MetaType1. <ftp://bop.eps.gda.pl/pub/metatype1>. This is used to create the excellent Latin Modern font family (*CTAN:/fonts/lm*), which extends Computer Modern to a vast repertoire of scripts.
- Editing of bitmap fonts: Xbfe from the GNU font utilities mentioned below; the X BDF-editing programs available from <ftp://ftp.x.org/R5contrib/xfed.tar.Z> and <ftp://ftp.x.org/R5contrib/xfedor.tar.Z>; and finally, if your fonts have only 128 characters, you can use the old gftopx1, pxtouch, and chtopx programs from <ftp://ftp.tug.org/tex/web>.
- Editing of outline fonts: FontForge, <fontforge.sourceforge.net>. This is a very elaborate program with support for many outline formats (Type 1, OpenType, TrueType, ...), and many advanced font editing features.
- PK bitmaps from PostScript outline fonts: gsftopk from the ‘xdvi’ distribution. Alternatively, ps2pk, from *CTAN:/fonts/utilities/ps2pk*.
- PostScript Type 1 font format conversion (i.e., between PFA and PFB formats): <https://www.lcdf.org/type>.
- Tracing bitmaps to fitted outlines: Autotrace (<http://autotrace.sourceforge.net>), Potrace (<http://potrace.sourceforge.net>). For Metafont fonts, either of the two programs mftrace (<http://www.xs4all.nl/~hanwen/mftrace>) or textrace (<http://textrace.sourceforge.net>) make the job easier.
- Virtual font creation: <https://ctan.org/pkg/fontinst>.

Appendix A Legalisms

In general, each file has its own copyright notice stating the copying permissions for that file. Following is a summary.

The Stanford TeX programs and Web2c system itself are in the public domain (<https://tug.org/texlive/copying.html>). The sources may be copied verbatim, or used as the starting point of new software under different names; however, per the wishes of the authors, they should be modified only through a .ch file, but this is in the nature of a development request rather than a legal requirement.

MLTeX, pdfTeX, LuaTeX, XeTeX, and all the other derived engines have used various license terms for their additions to the base code, often the GPL (see <https://www.gnu.org/licenses/#GPL> or (for example) the file `web2c/pdftexdir/COPYINGv2`. They also mostly make use of additional libraries with their own (compatible) terms. Please see each program's sources.

The Kpathsea library is covered by the GNU Lesser General Public License (see Section “Introduction” in *Kpathsea*). Therefore, the *binaries* resulting from a standard Web2c compilation are also covered by the LGPL; so if you (re)distribute the binaries, you must also (offer to) distribute the complete source that went into those binaries. See <https://gnu.org/licenses/#LGPL> or the file `kpathsea/COPYING.LESSERv2`.

Appendix B References

1. Kpathsea: See *Kpathsea*.
2. Dvips and Afm2tfm: See *Dvips*.
3. The TeX Users Group: <https://tug.org>. For an introduction to the TeX system, see <https://tug.org/begin.html>.
4. TUGboat, the principal journal for the TeX world: <https://tug.org/TUGboat>.
5. TeX and computer typesetting in general:
<ftp://ftp.math.utah.edu/pub/tex/bib/texbook1.bib>.
6. For a bibliography of formal articles and technical reports on the TeX project, see the books *TeX: The Program* or *Metafont: The Program* cited below.
7. [Bil87] Neenie Billawala. Write-white printing engines and tuning fonts with Metafont. *TUGboat*, 8(1):29–32, April 1987. <https://tug.org/TUGboat/tb08-1/tb17billawala.pdf>.
8. [Hob89] John D. Hobby. A Metafont-like system with PS output. *TUGboat*, 10(4):505–512, December 1989. <https://tug.org/metapost>.
9. [Hob92] John D. Hobby. A User’s Manual for MetaPost. Technical Report CSTR-162, AT&T Bell Laboratories, 1992.
10. [Hob93] John D. Hobby. Drawing Graphs with MetaPost. Technical Report CSTR-164, AT&T Bell Laboratories, 1993.
11. [HS91] Samuel P. Harbison and Guy L. Steele Jr. *C—A Reference Manual*. Prentice-Hall, Upper Saddle River, NJ 07458, USA, third edition, 1991. An authoritative reference to the C programming language, and a good companion to Kernighan and Ritchie.
12. [KL93] Donald E. Knuth and Silvio Levy. *The CWEB System of Structured Documentation, Version 3.0*. Addison-Wesley, Reading, MA, USA, 1993. <https://ctan.org/pkg/cweb>.
13. [Knu84] Donald E. Knuth. A torture test for TeX. Report No. STAN-CS-84-1027, Stanford University, Department of Computer Science, 1984.
14. [Knu86a] Donald E. Knuth. A Torture Test for METAFONT. Report No. STAN-CS-86-1095, Stanford University, Department of Computer Science, 1986.
15. [Knu86b] Donald E. Knuth. *The TeXbook*, volume A of *Computers and Typesetting*. Addison-Wesley, Reading, MA, USA, 1986.
16. [Knu86c] Donald E. Knuth. *TeX: The Program*, volume B of *Computers and Typesetting*. Addison-Wesley, Reading, MA, USA, 1986.
17. [Knu86d] Donald E. Knuth. *The METAFONTbook*, volume C of *Computers and Typesetting*. Addison-Wesley, Reading, MA, USA, 1986.
18. [Knu86e] Donald E. Knuth. *METAFONT: The Program*, volume D of *Computers and Typesetting*. Addison-Wesley, Reading, MA, USA, 1986.
19. [Knu86f] Donald E. Knuth. *Computer Modern Typefaces*, volume E of *Computers and Typesetting*. Addison-Wesley, Reading, MA, USA, 1986.
20. [Knu89] Donald E. Knuth. The errors of TeX. *Software—Practice and Experience*, 19(7):607–681, July 1989. This is an updated version of Knuth:1988:ET.

21. [Knu90] Donald Knuth. Virtual Fonts: More Fun for Grand Wizards. *TUGboat*, 11(1):13–23, April 1990. <https://tug.org/TUGboat/tb11-1/tb27knut.pdf>.
22. [Knu92] Donald E. Knuth. *Literate Programming*. CSLI Lecture Notes Number 27. Stanford University Center for the Study of Language and Information, Stanford, CA, USA, 1992.
23. [Lam94] Leslie Lamport. *L^AT_EX: A Document Preparation System: User’s Guide and Reference Manual*. Addison-Wesley, Reading, MA, USA, second edition, 1994. Reprinted with corrections, 1996.
24. [Lia83] Franklin Mark Liang. Word hy-phen-a-tion by com-pu-ter. Technical Report STAN-CS-83-977, Stanford University, August 1983. <https://tug.org/docs/liang/liang-thesis.pdf>.
25. [Mac91] Pierre A. MacKay. Looking at the pixels: Quality control for 300 dpi laser printer fonts, especially Metafonts. In Robert A. Morris and Jacques Andre, editors, *Raster Imaging and Digital Typography II—Papers from the second RIDT meeting, held in Boston, Oct. 14–16, 1991*, pages 205–215, New York, 1991. Cambridge University Press.

Index

"	
" character, ignored in filenames	14
#	
'#define' options	3
\$	
\$ expansion in filenames	14
%	
%& magic number	12
-	
- starting a filename	6
- starts option names	6
-- starts option names	6
--disable-dump-share configure option	12
--disable-mf-nowin	29
--enable-epsfwin	29
--enable-hp2627win	29
--enable-ipc configure option	17
--enable-mftalkwin	29
--enable-next	29
--enable-regiswin	29
--enable-suntoolswin	29
--enable-tektronixwin	29
--enable-unitermwin	29
--help common option	6
--verbose common option	6
--version common option	6
--with-editor=cmd	13
--with-mf-x-toolkit=kit	29
--with-x	29
-8bit	8
-base=base	12
-base=dumpname	7
-change=chfile	31
-charcode-format=type	50, 52
-cnf-line	6
-D compiler options	3
-disable-write18	18
-dpi=real	42
-enable-write18	18
-enc	17
-file-line-error	6
-file-line-error-style	6
-fmt=dumpname	7
-fmt=fmt	12
-geometry, supported with Xt	29
-halt-on-error	7
-images	48
-ini	7, 11
-interaction=string	7
-ipc	17
-ipc-start	17
-jobname=string	7
-kpathsea-debug=number	7
-length=number	38
-loose	39
-lowercase	38
-magnification=integer	41, 42
-max-pages=n	41, 42
-mem=dumpname	7
-min-crossrefs=n	36
-mixedcase	38
-mktex=filetype	17, 27
-mltex	17
-mnemonics	48
-no-file-line-error	6
-no-mktex=filetype	17, 27
-no-parse-first-line	7
-no-shell-escape	18
-output-comment=string	18
-output-directory	7, 8
-output-level=n	42
-overflow-label-offset=points	30
-page-start=page-spec	41, 42
-parse-first-line	7
-progname=string	7, 12
-recorder	7
-shell-escape	18
-shell-restricted	18
-show-opcodes	42
-strict	39
-style=mftfile	32
-T	35
-terse	36
-tex=texprogram	35
-translate-file=tcxfile	8
-troff	35
-underline	38
-uppercase	38
-x	39

.	
. ., used for output.....	8
.2602gf	26
.aux cross-reference files	36
.base.....	27
.bb1 bibliography files	36
.bib bibliography databases.....	36
.blg BibTEX log file	36
.fmt	18
.mf	26
.mp	33
.mps files and PDF	34
.nnn PostScript figures.....	33
.nnngf generic fonts	26
.tcx character translation files.....	8, 21
.tex	16
.tfm output	26, 33
.Xdefaults	29
.Xresources	29
^	
^^ notation, avoiding.....	22
\	
\bibliography	36
\bibliographystyle.....	36
\charchardef and MLTEX	20
\countn.....	41, 42
\font and dynamic generation	16
\fontdimen.....	51
\immediate\write18.....	23
\input braced (grouped) filename	14
\input filename caveats.....	14
\input filenames.....	13
\input quoted filename	14
\input, and pipes	24
\mag	41, 42
\openin, and pipes.....	24
\openout and security	16
\openout, and pipes	24
\output routine, and \write.....	23
\pdfshellescape	24
\string, and \input filenames.....	15
\tracingcharchardef and MLTEX	21
\tracinglostchars and MLTEX	21
\write18 shell escape extension	23
~	
~ expansion in filenames	14
2	
2602gf	26

8

8 bit clean	8
8 bit clean output, specifying.....	8
8-bit characters	21

A

abrv bst	37
accented character	21
accents, hyphenating words with	20
acknowledgements	1
acm bst	37
Ada, WEB for	38
additional Make targets	4
AFM to TFM conversion	53
afm2tfm	53
afmtopl	53
Aleph.....	25
aliases for fonts	8
alpha bst	37

American Mathematical Society,
typesetting system

AMSTEX	19
apalike bst	37
architecture dependencies	12
array limit, fixed	10
array sizes	10
assembly language routines	4
autotrace	53
Awk, WEB for	38

B

base file, determining	12
base files	27
base files, need mode definitions	28
base files, plain only	28
base files, sharing	12
bases Make target	4
basic BibTEX style files	37
basic fonts and macros	2
batch languages	16
BDF and GF conversion	53
beamer, package	20
beginfig	33
Berry, Karl	1
BIBINPUTS, search path for bib files	36
bibliographies, creating	36
bibliography	55
bibliography items, cross-referenced	36
BibTEX	36
bibtex	36
BibTEX collection	36
BibTEX style files	37
BigEndian machines	12
binaries, linking	7
blank lines, in TCX files	22
boxes, memory for	10

braced filename for `\input` 14
breakpoints, memory for 10
Breitenlohner, Peter 1
`BSTINPUTS`, search path for bst files 36
`btx` for MetaPost labels 33
`btxdoc.bib` 36
`btxdoc.tex` 36
`btxhak.tex` 36
byte position 47, 49
byte swapping 12

C

`c-sources` Makefile target 4
caveats for `\input` filenames 14
change files, and MFT 31
change files, and Tangle 38
change files, and Weave 39
changing error messages style 6
character codes, in GFtype output 49
character codes, in PKtype output 47
character codes, in TCX files 22
character proofs of fonts 30
`CHARACTER` property 51
character translation files 21
`CHARDP` property 51
`CHARHT` property 51
`CHARIC` property 51
`CHARWD` property 51
`chtopx` 53
class name for Metafont 29
`cm.base` 28
`cmbase.mf` 28
`cmbase.mft` 32
`cmmf.base` not recommended 28
color, in DVItoMP 35
comments, in TCX files 22
comments, MFT control 31
common options 6
commonalities 6
compilation 2
compile-time options 2, 3
Computer Modern fonts, and Troff 34
Computer Modern macros 28
Computer Modern Typefaces, production of 32
configuration 2
configuration file reading 8
configuration file values 10
configuration, compile-time 2
`configure --with/--enable` options 2
`CONTENTS.tex` 39
ConTeXt 19
conventions for options 6
conversion, DVI to plain text 41
conversion, GF to PK 46
conversion, GF to plain text 48
conversion, PK to GF 46
conversion, PK to plain text 46

conversion, property list to TFM 52
conversion, property list to VF 53
conversion, TFM to property list 50
conversion, VF to VPL 52
copyright notices 54
Cork encoding and ISO input 22
creating memory dumps 11
cross-referenced bibliography items 36
cross-references, omitting 39
current directory, used for output 8
Curtis, Pavel 1
`CWEB` 38
`Cweb` 38

D

date and time, in memory dumps 12
debugging DVI utilities 42
debugging flags, specifying 7
decimal character codes, in TCX files 22
dependencies, hardware 12
design-size units 51
device definitions, for Metafont 28
device-independent width 47, 49
directory structure 2
`DISPLAY` 29
dot files, written by TeX programs 16
double quote character, ignored in filenames 14
downloading of fonts for MetaPost labels 34
`DrawingServant` 29
dump file 7
dumping memory 11
DVI comment, specifying 18
DVI files, converting to MPX 35
DVI files, explained 45
DVI format definition 41
DVI opcodes, showing 42
DVI utilities 41
`dvcopy` 41
`dvitomp` 35
`dvitype` DVI validation 41
`dvitype` output example 42
`dvitype.web` 41
dx horizontal escapement 47, 49
dy vertical escapement 49
dynamic array allocation 10
dynamic Metafont mode
 definitions with `smode` 28
dynamic packing variable 47

E

- e** response at error prompt 13
- e-circumflex** 21
- e-T_EX** 25
- e.mft** 32
- EC fonts 16, 26
- editing of bitmap fonts 53
- editor invoked at error 13
- eight-bit characters in filenames 14
- empty.tcx** 22
- endian dependencies 12
- eoc** GF command 49
- Eplain** 20
- epsf** 29
- epT_EX** 25
- errors, editor invoked at 13
- escapement, horizontal 47, 49
- escapement, vertical 49
- etex** for MetaPost labels 33
- etex** is pdfT_EX 25
- eupT_EX** 25
- executables, shared initial and virgin 11
- exit status, of shell escape 24
- expand_depth** 10
- expanded plain format 20
- expansion limit, recursive 10
- expansion, and \input filenames 14
- extensions to T_EX 24
- extra_mem_bot** 10

F

- FACE** property 51
- FAMILY** property 51
- Ferguson, Michael 20
- file formats for fonts 45
- file recorder 7
- filename conventions, in input files 13
- filenames starting with ‘-’ 6
- first line of the main input file 8
- fixed-point arithmetic 4
- FIXPT** 4
- flag byte 47
- floating-point arithmetic 4
- floating-point values 12
- fmt file, determining 12
- fmt files 18
- fmt files, sharing 12
- fmts** Make target 4
- font aliases 8
- font character code, translating 23
- font design 26
- font downloading for MetaPost labels 34
- font file formats 45
- font proofs 30
- font utilities 45
- font utilities, non-Web2c 53
- fontforge** 53

- fontinst**, for creating virtual fonts 53
- fonts, basic 2
- format files 19
- formats for T_EX 19
- formats** Make target 4
- fraction routines 4
- Free Software Foundation
 - documentation system 19
 - freedom of Web2c 1
 - ftp.math.utah.edu** 36

G

- generating source specials 18
- geometric designs 26
- geometric font scaling 45
- geometry for Metafont 29
- getopt_long_only** 6
- GF files, explained 45
- GF files, output by Metafont 26
- GF format definition 45
- GF output 26
- GF, converting PK to 46
- GF, converting to PK 46
- gftodvi** 30
- gftopk** 46
- gftopxl** 53
- gftype** GF validation 48
- gftype.web** 45
- glue ratio representations 12
- glue, memory for 10
- glyph substitutions 20
- gray font 30
- group-delimited filename for \input 14
- Gruff, Billy Goat 4
- gsftopk** 53

H

- Harbison, Samuel P. 12
- hardware and memory dumps 12
- headerbyte** information 51
- height, in pixels 47
- help, online 6
- Herberts, Mathias 29
- hex character codes, in TCX files 22
- history 1
- Hobby, John 1
- horizontal escapement 47, 49
- hp2627** 29
- human languages, supported in T_EX 20
- human-readable text, converting DVI to 41
- human-readable text, converting GF to 48
- human-readable text, converting PK to 46
- human-readable text, converting TFM to 50
- human-readable text, converting VF to 52
- hypertext 25
- hyphenation and languages 20

hyphenation patterns, creating 23

I

ice cream 1
identifier case 38
identifier collisions 39
identifier length 38
identifiers with underlines 38
ieeetr.bst 37
il1-t1.tcx 22
il2-t1.tcx 22
Info format 19
initial form, enabling 7
initial Metafont 27
initial MetaPost 35
initial programs 11
initial TeX 18
initializations, lengthy 11
input filenames 13
install-bases Make target 4
install-fmts Make target 4
install-formats Make target 4
install-mems Make target 4
installation 2
interaction between TCX files and ‘-8bit’ 23
interaction mode 7
international characters 21
introduction 1
IPC 24
IPC_DEBUG 4, 24

J

job name 7

K

kerning table, in TFM files 51
keyboard character code, translating 23
Knuth, Donald E. 1, 31
KPATHSEA_DEBUG 7
KRN property 51

L

label font 30
LABEL property 51
language support in TeX 20
languages, hyphenation rules for 23
LATEX 19
Latin Modern 53
left side bearing 47, 49
legalisms 54
libsigsegv library 10
licensing terms 1
LIG property 51
ligature table, in TFM files 51

LIGTABLE property 51
linking binaries 7
links to binaries 12
literate programming 38
LittleEndian machines 12
location of *texmf.cnf* in TeX Live 10
log file, BibTeX 36
Lua 25
LuaTeX 25

M

machine dependencies 12
machine-readable, converting
 property lists to 52, 53
MacKay, Pierre 46
macro packages, major TeX 19
macros, basic 2
macros, predefining in memory dumps 11
magnification 41, 42
main_memory 10
Make targets, additional 4
Martin, Rick 1
Mathematical Reviews 19
mathematical typesetting 16
mem file, determining 12
mem files, sharing 12
memory dump to use, determining 12
memory dumps 11
memory dumps and hardware 12
memory dumps, contain date and time 12
memory dumps, creating 11
mems Make target 4
meta characters in filenames 14
Metafont 26
Metafont geometry 29
Metafont graphics 29
Metafont input files 26
Metafont invocation 26
Metafont meets PostScript 33
Metafont online support, new devices 29
Metafont source, prettyprinting 31
Metafont, compatibility in MetaPost 35
Metafont, initial 27
Metafont, MetaPost, and TeX 10
MetaPost 33
MetaPost and plain Metafont compatibility 35
MetaPost input files 33
MetaPost invocation 33
MetaPost source, prettyprinting 32
MetaPost, initial 35
MetaPost, TeX, and Metafont 10
metatype1 53
mf 26
mf.base 27
MFEDIT 13
mfplain 35
mfput 26

mft	31
mftalk	29
MFTERM	29
mftmac.tex	31
micro-typography.....	25
mktexmf , disabling.....	26
mktexfM , disabling.....	16
mltex	20
MLT_EX , enabling.....	17
mode needed to run Metafont.....	26
mode_def	28
mode_setup	28
modes file needed for Metafont.....	28
modes.mf recommended modes file.....	28
modifying texmf.cnf in T_EX Live.....	10
Morgan, Tim	1
Morris, Bob.....	1
MPEDIT	13
mpgraph.pdf	33
mpman.pdf	33
mpost	33
mpost , reason for name change.....	2
mpout	33
mproof.tex	34
mptrap Make target.....	4
mptrap test.....	4
mptrap.readme	4
MPX files, converting from DVI files.....	35
Multi-lingual T_EX	20
multiple spaces, and \input filenames.....	14
N	
N tilde.....	21
new graphics support for Metafont	29
newrow GF command	49
next	29
NO_X11WIN	29
non-Unix system, compiling on.....	4
non-windows-capable Metafont.....	29
NUL, not allowed in filenames.....	14
O	
octal character codes, in TCX files	22
offset for overflow labels.....	30
Omega	25
online Metafont graphics.....	29
opcodes, showing DVI.....	42
OpenType support.....	25
optical font scaling.....	45
option conventions	6
origin.....	47
output directory, specifying.....	7, 8
output file location.....	8
output files, written by T_EX programs.....	16
output_comment for DVI files	18
overflow label offset.....	30
overflow, of runtime stack	10
P	
packet length	47
page, starting	41, 42
parsing the first line.....	7
Pascal, creating from WEB	38
patgen	23
path searching	8
path searching debugging	7
PDF	25
PDF, and .mps files	34
pdfT_EX	25
permissions, legal	54
PFA and PFB conversion	53
pfaedit	53
PiCT _E X, increasing memory for	10
pipes, reading and writing	24
pixel height	47
pixel width	47
PK bitmaps from PostScript	53
PK files, explained	45
PK files, not output by Metafont	26
PK format definition	45
PK, converting GF to	46
PK, converting to GF	46
pktogf	46
pkttype PK validation	46
pktype.web	45
PL files, explained	45
plain Metafont, compatibility in MetaPost	35
plain text, converting DVI to	41
plain text, converting GF to	48
plain text, converting PK to	46
plain text, converting TFM to	50
plain text, converting VF to	52
plain.base	27
plain.bst	37
plain.fmt	19
plain.mft	32
pltotf	52
pool file, writing	38
Poole, Simon	29
pooltype	39
portable filenames	14
PostScript fonts, and Troff	34
PostScript meets Metafont	33
PostScript output	33
PostScript to PK bitmaps	53
PostScript Type 1 font conversion	53
PostScript, and font scaling	45
potrace	53
predefined macros and memory dumps	11
prettyprinting Metafont source	31
prettyprinting WEB programs	39
primitives, new	25
printable characters, specifying	22

printer characteristics, for Metafont	28
production use	11
program name, determines memory dump	12
program names, special	7, 17
prologues	35
prologues , and EPSF output	34
proof mode	26
proof sheets, of fonts	30
property list format	50
property list, converting TFM to	50
property list, converting VF to virtual	52
ps2pk	53
psfonts.map , read by MetaPost	34
pTeX	25
PXL files, explained	45
pxtoch	53
 Q	
quoted filename for <code>\input</code>	14
 R	
Raichle, Bernd	20
reading, additional	1
readonly directory, running T_EX in	8
reallocation of arrays	10
recursive expansion limit	10
redefined character substitutions	21
reference pixel	47
references	55
regis	29
Regis graphics support	29
regression testing	18
repeated rows	48
representation of strings	40
restricted shell escapes	23
right side bearing	47, 49
Rokicki, Tomas	1
run length encoded bitmaps	48, 49
runtime options	10
runtime stack overflow	10
 S	
scaled pixels	47, 49
scaling of fonts	45
security, and <code>\openout</code>	16
security, and output files	16
security, and shell escapes	23
security, and <code>write</code>	34
segmentation fault	10
shapes	26
sharing memory dumps	12
shell commands in T_EX	23
<code>shell_escape</code> enabling in T_EX	23
<code>shell_escape_commands</code>	24
siam.bst	37
side bearings	47, 49
SIGSEGV	10
slant font	30
slides, producing	20
SliT_EX	20
small Metafont memory and modes	28
smode and dynamic Metafont mode definition ..	28
sockets	24
space-terminated filenames	13
Spiderweb	38
Stallman, Richard	1
starting page	41, 42
Steele Jr., Guy L.	12
stopping at the first error	7
strategy, overall	1
string numbers, displaying	39
string pool, writing	38
string representation	40
style design, for Bib T_EX	36
style files	32
substitutions of font glyphs	20
sun	29
sun-gfx.c	29
Suntools	29
SunView	29
swap space, as array limit	10
swapping bytes	12
syntax of TCX files	22
system C library function	23
system command	23
system fonts, using	25
 T	
T_EX encoding and ISO input	22
tabs, and <code>\input</code> filenames	14
Tachikawa, Elizabeth	46
tangle	38
targets, additional Make	4
TCX character translation files	21
technical illustrations, creating	33
tek	29
Tektronix	29
Tektronix 4014	29
TERM	29
terminator for filenames	13
terse output	36
tex	16
T_EX , bibliographies for	36
T_EX , creating from Metafont	31
T_EX , creating from WEB	39
T_EX , description of	16
T_EX , extensions to	24
T_EX , format packages for	19
T_EX , initial	18
T_EX , input files found	16
T_EX , invocation	16
T_EX , Metafont, and MetaPost	10

T_EX, Web2c implementation of 1
tex fmt 19
TEXBIB, search path for bib files 36
TEXEDIT 13
texfonts.map 8
Texinfo 19
texmf.cnf 8, 10
texmf.cnf for editors 13
texmf.cnf for shell escapes 23
texmf_casefold_search 10
texmfmp.c 29
TEXMFOUTPUT, used for reading 8
TEXMFOUTPUT, used if ‘.’ unwritable 8
texput 16
TFM files, converting property lists to 52
TFM files, explained 45
TFM files, output by Metafont 26
TFM files, output by MetaPost 33
TFM width of characters 47, 49
tftopl 50
three programs 10
time and date, in memory dumps 12
title font 30
tokenization, and `\input` filenames 14
toolkits, X 29
torture tests 4
translation file for T_EX, specifying 8
translation from WEB to C 1
trap Make target 4
trap test 4
trapman.tex 4
Trickey, Howard 1
trip Make target 4
trip test 4
tripman.tex 4
triptrap Make target 4
Troff, and MetaPost 34
troff, supported in MetaPost 33
Troff, WEB for 38
Trojan horses and T_EX programs 16
TrueType support 25
TUGboat bibliography 36
Type 1 conversion 53
type design, personal 28
type programs, DVI 41
type programs, GF 48
type programs, PK 46
type programs, pool 39
typeface families 26
typesetting 16

U

Unicode 25
Unicode input 17
Unicode input, native 25
uniterm 29
unsrt bst 37
upT_EX 25
UTF-8 input 17
UTF-8 input, native 25

V

validation, of DVI files 41
validation, of GF files 48
validation, of PK files 46
validation, of TFM files 50
validation, of VF files 52
verbose BibT_EX output, suppressing 36
verbosity, enabling 6
version number, finding 6
vertical escapement 49
VF files, converting property lists to 53
vftovp 52
virgin programs 11
virtual font creation 53
virtual fonts, expanding 41
virtual-fonts.knuth 45
virtualfonts.txt 45
vptovf 53

W

weave 39
WEB 38
web environments, and security 24
WEB pool files, displaying 39
WEB programs, compiling 38
WEB programs, typesetting 39
WEB2C, search path for TCX files 22
Weber, Olaf 1
webmac.tex 39
webman.tex 38
whitespace, in TCX files 22
whitespace-terminated filenames 13
width, device-independent 47, 49
width, in pixels 47
word processor, not 16
writing memory dumps 11

X

X bitmap fonts	53
X class name for Metafont	29
x offset	47
X resources	29
X toolkits and Metafont	29
xampl.bib	36
xbfe , bitmap font editor	53
Xe ^T E _X	25
xfed , bitmap font editor	53

xfedor, bitmap font editor

53

Xlib

29

Xlib support

29

Xt

29

Xt support

29

xterm

29

y offset

47

Y